## NOTICE TO WATER WELL CONTRACTOR The original and first copy of this sport of are to be filed with the WATER RESOURCES DEPARTMENT. SALEM, OREGON 9731 within 30 days from the day of well completion.

## WATER WELL REPORT

## STATE OF OREGON

(Please type or print)

(Do not write above this line)

State	Well No	o	155/10E-366	-
State	Permit	No.	***************************************	-

(1) OWNER;	(10) LOCATION OF WELL:
Name Dick Max	County Deschutes Driller's well number
Address Sister's Ore.	N.W. N. W. Section 3 T. /S SR. /O.E. W.M.
(a) MVDV OF WORK (11).	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	Tract, Reger
New Well Deepening Reconditioning Abandon Abandon	Barthey Phace
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.
Rotary   Driven   Domestic X Industrial   Municipal	Static level 98 ft. below land surface. Date 8-27-79
□ Bored □ Irrigation □ Test Well □ Other □	Artesian pressure Ibs. per square inch. Date
(5) CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Diameter of well below casing 6"
" Diam. Fromft. toft. Gage	Depth drilled $109$ ft. Depth of completed well $109$ ft.
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials;
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
(6) PERFORATIONS: Perforated?  Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Water Bearing Red
perforations from ft. toft.	and Black tinder's 102 109 98
perforations from ft. to ft.	
perforations fromft. toft.	
(7) SCREENS: Well screen installed	
Manufacturer's Name	
Type Model No.	
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	DECEIVED
(8) WELL TESTS: Drawdown is amount water level is	NEOFIAED
TOWELER DELOW BLANC LEVEL	FEB 11980
Was a pump test made?  Yes No If yes, by whom?	WATER RESOURCES DEPT
eld: gal./min. with ft. drawdown after hrs.	SALEM OREGON
ii "	
" " "	)
Bailer test / gal./min. with Oft. drawdown after hrs.	
tesian flow g.p.m.	C 27 79 6-27 70
Remperature of water Depth artesian flow encountered ft.	Work started 9-23 19 79 Completed 8-27 1979
(9) CONSTRUCTION:	Date well drilling machine moved off of well 8 - 2 7 1979
(9) CONSTRUCTION: Well seal—Material used // Dist	Drilling Machine Operator's Certification:
Well sealed from land surface to ft.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my
Diameter of well bore to bottom of seal in,	best knowledge and belief.
Diameter of well bore below seal in.	[Signed] Wayne T. Suchnel Date 27, 19 A.
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 987
How was cement grout placed?	
All I all and a second a second and a second a second and	Water Well Contractor's Certification:
A STATE OF THE STA	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and, belief.
Was a drive shoe used?   Yes No Plugs Size: location ft.	$\mathcal{L}$
Did any strata contain unusable water? Tyes No	Name (Person, firm of corporation) (Drue or print)
Type of water? depth of strata	Address 3361 NE. DNe/Lwgy Red. One
Method of sealing strata off	[Signed] Wayne T. Buchner
Was well gravel packed?   Yes No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 677 Date 8-27 , 1979