The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 9411 STATE ENGINEER, SALEM, OREGON 9411 NG (Do not write above this line) of well completion.

(11) LOCA

State Well No. 15/10 - 10

State Permit No. ......

(1) OWNER: Name / AZY Z RANCH	(11) LOCATION OF WELL:  County Deschars Driller's well number		
Address SisTers Oregin	14 14 Section 16 T.15	R. 10E	W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivisio	n corner	<del></del>
• • • • • • • • • • • • • • • • • • • •			
New Well Deepening Reconditioning Abandon Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(12) WELL LOG: Diameter of well below casing 12		
Cable Jetted Domestic Industrial Municipal	Depth drilled 168 ft. Depth of completed well 165 ft.		
Dug	Formation: Describe color, texture, grain size and structure of materials;		
CASING INSTALLED: Threaded Welded	and show thickness and nature of each stratu with at least one entry for each change of form		
12 " Diam. from 72 ft. to 165 ft. Gage 9250	in position of Static Water Level as drilling pro		
Tiam, from ft, to ft, Gage	MATERIAL	From To	SWL
" Diam, from ft. to ft. Gage	SANDY TOPSOIL	0 1	
PERFORATIONS: Perforated? Yes   No.			
Type of perforator used Torch	ZARGE BOULDERS	1 10	<u>-</u>
Size of perforations 1/2 in. by 8 in.			÷.
185 perforations from 14.5 tt. to 16.5 tt.	GREN LAVA (MED)	10 27	
perforations from ft. to ft.			='
perforations fromft. toft.	RED CINDERS + GRAVEL	27 30	<del></del>
perforations fromft. toft.	1304 PACHA (1400)	30 52	<u></u>
perforations fromft, toft.	GREY BASALT (HARD)	3052	<del></del> .
	BROWN CHAY + GRAVEL	5286	
(7) SCREENS: Well screen installed?   Yes No	BHOLDIN CHAY I GATOLE	02 30	
Manufacturer's Name	GREY BASALT (HARD)	86 122	
Type	The second secon	, i	
Diam. Slot size Set from ft. to ft.  Diam. Slot size Set from ft. to ft.	RED CINDERS	122 652	144
Diam. Stot size Set from it. to it.		- '	
(8) WATER LEVEL: Completed well.	GREY BASALT (HARD)	152 156	144
Static level 44 ft. below land surface Date 5/13/70		1 1 1 1	111/
sian pressure lbs. per square inch Date	ZARGE BOULDERS	156 168	194
(9) WELL TESTS: Drawdown is amount water level is		<del>                                     </del>	- · · -
lowered below static level			
Was a pump test made? Yes No If yes, by whom? Dury P. Paux	Work started 3/26 1970 Complet	ed \$//3	1970
Yield: 300 gal./min. with 2 ft. drawdown after if hrs.	Date well drilling machine moved off of well	5/17	167
" "	Date wen drining machine moved off of wen	3//3	19/61
" " " " " "	Drilling Machine Operator's Certification:		
Bailer test gal./min. with ft. drawdown after hrs.	This well was constructed under my drials used and injormation reported about		
Artesian flow g.p.m. Date	knowledge and belief.	7 - 7	-
Temperature of water 5/ Was a chemical analysis made? Yes No	[Signed] (Drilling Machine Operator)	*Date 5/13	, 19 <b>2.</b> C
(10) CONSTRUCTION:	-	210	
Well seal-Material used BENTONITES DRIFF CATTING	Drilling Machine Operator's License No.	<i>&gt;</i> 7 <i>\</i>	
Depth of seal 30 ft.	Water Well Contractor's Certification:		
Diameter of well bore to bottom of sealin,	This well was drilled under my jurisdiction and this report is		
Were any loose strata cemented off?   Yes No Depth	true to the best of my knowledge and belief.		
Was a drive shoe used? ☐ Yes 💢 No	NAME PICH AFINS WEFT PRIFTING (Person, firm or corporation) (Type or print)		
Did any strata contain unusable water?   Yes No	111 Pa 3-2 2/11	PRINEIN	41-5
Type of water? depth of strata	Address 1.0 0 7	k-14: 11: 11: 15: 15:	754
Method of sealing strata off	[Signed] Alleh (Ske)	ns	/
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	(Water Well Contra	ctor)	
Gravel placed fromft. toft.	Contractor's License No. 220 Date	5//6	1970
•			