NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORTE E CEIVED AND STATE OF OREGON

(Please type or print)

other	3		-
Wathe	1.00	· ands	_
145	1136	- Wood	

(Please type or print)

(Do not write above this line)

VATER RESOURCES DEPT: 6-10207

(1) OWNER:	(10) LOCATION OF WELL:
Name Bims Enterprises - Stacy Johnson	
Address Terrebonne, Ore. 97760	County Deschutes Driller's well number SE 1/4 SW 1/4 Section 20 T. 14S R. 13E W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well Deepening Reconditioning Abandon	Lot 7 Block 2 - First Edition Cinder Butte Estates
If abandonment, describe material and procedure in Item 12.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.
Rotary M. Driven D	Depth at which water was first found 200 ft.
Cable	Static level 185 ft. below land surface. Date 1/9/78
Dug	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Public Water Supply Threaded Welded	(40)
10 " Diam. from 1 ft. to -21 ft. Gage .250	(12) WELL LOG: Diameter of well below casing 0
8 " Diam. from 1 ft. to -229 ft. Gage .188	Depth drilled 229 ft. Depth of completed well 229 ft.
	Formation: Describe color, texture, grain size and structure of materials;
	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used factory torch	MATERIAL From To SWL
Size of perforations 7 in. by in.	brown sandy soil 0 2
160 perforations from -189 ft. to -229 ft.	red soft rock 2 4
perforations from ft. to ft.	grey soft lava rock 4 7
perforations from	red soft rock 7 10
(7) SCREENS: Well screen installed? ☐ Yes ♣ No	brown coarse sandstone 10 29
Manufacturer's Name	red soft broken rock 29 38
Type Model No.	red coarse cinders & small boulders 38 55
Diam, Slot size Set from ft. to ft.	boulders 38 55 brown coarse sandstone 55 77
Diam Slot size Set from ft. to ft.	black fine sandstone 77 125
(8) WELL TESTS: Drawdown is amount water level is	brown coarse sandstone 125 154
lowered below static level	black hard broken rock 154 200 185
Was a pump test made? 🗌 Yes 🏋 No If yes, by whom?	black hard broken rock WB 200 229
yild: gal./min. with ft. drawdown after hrs.	
" " " "	
" " "	
Bailer test 25 gal./min. with no ft. drawdown after 1 hrs.	
Artesian flow g.p.m.	
rature of water Depth artesian flow encountered ft.	
The state of the s	Work started 1-4 1978 Completed 1-10 1978
(9) CONSTRUCTION:	Date well drilling machine moved off of well 1-10 1978
Well seal—Material used Cement	Drilling Machine Operator's Certification:
Well sealed from land surface to ft.	This well was constructed under my direct supervision
Diameter of well bore to bottom of seal in.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal in.	[Signed] Wale Paul Dum Date 1-17 19 78
Number of sacks of cement used in well seal	(Drilling Machine Operator)
How was cement grout placed?pressure grouted	Drilling Machine Operator's License No. 934
Constitution of the second of	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? ☐ Yes ⚠No Plugs Size: location ft,	true to the best of my knowledge and belief.
Did any strata contain unusable water? Yes No	Name Crawford Well Drilling
Type of water? depth of strata	(Person, firm or corporation) (Type or print) Address 1245 N. W. Lower Bridge Terrebonne, Ore.
Method of sealing strata off	Address 1240 M. W. Lower Bridge Terrebonne, Ore.
TV.	[Signed] Same O. Jan D.
	(water well Contractor)
ravel placed from ft. to ft.	Contractor's License No. 570 Date 1-17 , 19