NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the STATE OF OREGON JUL 2 8 1977 (Please type or print) STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date WATER RESOURCES DEFIT above this tree tate Permit No. ... of well completion. SALEM, ORECON (10) LOCATION OF WELL: (1) OWNER: Driller's well number County Deschutes Keith Cyrus т.15\$ п. 16 14 NW 14 Section 13 W.M. Address Star Rt Sisters OR Bearing and distance from section or subdivision corner 2191 (2) TYPE OF WORK (check): S % 39' Eof the NW corner of section New Well Reconditioning [Abandon 🗌 Deepening X If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found Driven 🗆 ft. below land surface. Date 7/2/77 Rotary D Domestic | Industrial | Municipal | Static level 180 Irrigation Test Well | Other Bored 🗌 Artesian pressure lbs. per square inch. Date CASING INSTALLED: Threaded [Welded 📆 (12) WELL LOG: Diameter of well below casing ... ft. to =42.2 ft. Gage 250" Depth drilled 254 ft. Depth of completed well Formation: Describe color, texture, grain size and structure of materials; " Diam. from and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. **PERFORATIONS:** Perforated? Yes Type of perforator used MATERIAL broken gray lava(water-bearing) Size of perforations in. by 253 perforations from ft. to 254 180 hard gray lava _____ perforations from _____ ft. to _____ ft. (7) SCREENS: Well screen installed?
Yes No Owner drilled well to 215' Manufacturer's Name and put in 42' of 18" grout ipe, grouting from 42 up to Diam. Slot size Set from 201 T grouted from 20' to Diam. Slot size Set from ft. to ft. and surface. Drawdown is amount water level is lowered below static level (8) WELL TESTS: er Was a pump test made? A Yes No If yes, by whom Roland gld: 5000 gal./min. with 2- ft. drawdown after 4 hrs. ,, Bailer test gal./min. with ft. drawdown after Artesian flow g.p.m. 19777 Completed 6/28 perature of water 50 Depth artesian flow encountered 19 77 Work started 1977 Date well drilling machine moved off of well (9) CONSTRUCTION: Well seal-Material used 26 sacks cement Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my Well sealed from land surface to best knowledge and/belief. [Signed] July (Milling Machine pperator) Diameter of well bore below seal _____in. Date 7/19 19.77 Number of sacks of cement used in well seal Drilling Machine Operator's License No. 440 Number of sacks of bentonite used in well seal Brand name of bentonite Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name THEOLOGIC WELLT DRIVETINGlbs./100 gals. Was a drive shoe used?

Yes No Plugs Size: location ft. (Person, firm or corporation) Did any strata contain unusable water?

Yes X No

Type of water?

Method of sealing strata off

depth of strata

Was well gravel packed? [] Yes No Size of gravel: .

Gravel placed from ft. to

Address Box 17 Terrebonne Or 97.760

(Mules

(Water Well Contractor)