

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

DESO 3/178

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

State Well No. 155/10E-26

State Permit No.

(1) OWNER:

Name David Orzdeck
Address 56467 N. BANK Rd. MCKENZIE BRIDGE 97401

(2) TYPE OF WORK (check):

New Well [x] Deepening [ ] Reconditioning [ ] Abandon [ ]
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [x] Cable [ ] Dug [ ] Driven [ ] Jetted [ ] Bored [ ]

(4) PROPOSED USE (check):

Domestic [x] Industrial [ ] Municipal [ ] Irrigation [ ] Test Well [ ] Other [ ]

CASING INSTALLED:

8" Diam. from 0 ft. to 30 ft. Gage 250
6" Diam. from 0 ft. to 70 ft. Gage 156

PERFORATIONS:

Type of perforator used TORCH
Size of perforations 6" in. by 1/8" in.
40 perforations from 55 ft. to 70 ft.

(7) SCREENS:

Well screen installed? [ ] Yes [x] No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? [ ] Yes [x] No
Yield: gal./min. with ft. drawdown after hrs.
Bailer test 25 gal./min. with 0 ft. drawdown after 2 hrs.

(9) CONSTRUCTION:

Well seal-Material used CEMENT SLURRY
Well sealed from land surface to 30 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 13 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? [ ] Yes [x] No
Did any strata contain unusable water? [ ] Yes [x] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [ ] Yes [x] No
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Deschutes Driller's well number
SE 1/4 NE 1/4 Section 26 T. 15S R. 10 E.W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 40 ft.
Static level 30 ft. below land surface. Date 12/30/75
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8"
Depth drilled 70 ft. Depth of completed well 70 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include: OLIVER BURDIEN (0-2), BOLD CONG. (2-5), GRAVEL (5-11), BOLD + CONG. (11-30), GRAVEL & CLAY (30-41), SAND & GRAVEL (41-70), WATER BEARING.

RECEIVED

JAN 07 1976

WATER RESOURCES DEPT. SALEM, OREGON

Work started 12/29/ 1975 Completed 12/30 1975
Date well drilling machine moved off of well 12/30 1975

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] [Signature] Date 12/31, 1975
(Drilling Machine Operator)

Drilling Machine Operator's License No. 487

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name McCoy & Son Well Drilling (Person, firm or corporation)
Address Rt. 2, Box 1167 Bevel, OR (Type or print)

[Signed] [Signature] (Water Well Contractor)

Contractor's License No. 599 Date 12/31, 1975