

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

RECEIVED **DESC 3232** **RECEIVED**
WATER WELL REPORT
STATE OF OREGON
DEC 18 1970 JAN 28 1971
STATE ENGINEER SALEM OREGON

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

(Please type or print) STATE ENGINEER SALEM OREGON
Write above this line Permit No. 15/11-7aa

(1) OWNER:

Name Charles Fenschel
Address State Route
Redmond, ORE, 97701

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded
6" Diam. from 0 ft. to 60 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom? McCoy
Yield: 15 gal./min. with 0 ft. drawdown after 2 hrs.
" " " " " "
" " " " " "
Bailer test 15 gal./min. with 0 ft. drawdown after 4 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used CEMENT
Well sealed from land surface to 0 to 60" ft.
Diameter of well bore to bottom of seal 9 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 6 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons
of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County DESCHUTES Driller's well number
NE 1/4 NE 1/4 Section 7 T. 15 R. 11 E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 355 ft.
Static level 355 ft. below land surface. Date 11-10-70
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8
Depth drilled 375 ft. Depth of completed well 375 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
BROWN TOP SOIL	0	4	
BOLDERS	4	28	
BROWN SANDSTONE	28	40	
GRAY LAVA ROCK	40	50	
BROWN SANDSTONE	50	120	
PINK LAVA	120	160	
BROWN SANDSTONE	160	285	
RED SANDSTONE	285	350	
GRAY LAVA	350	360	
SAND + GRAVEL	360	375	
WATER BEARING			

Work started 10-15 19 70 Completed 11-10 19 70
Date well drilling machine moved off of well 11-17 19 70

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] John H. McCoy Date 11-17, 19 70
(Drilling Machine Operator)
Drilling Machine Operator's License No. 541

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name John H. McCoy 11-17-70
(Person, firm or corporation) (Type or print)
Address Rt. 2, Box 1200 Bend Ore
[Signed] John H. McCoy
(Water Well Contractor)
Contractor's License No. 480 Date 11-18, 19 70