

The original and first copy of this report are to be filed with the

RECEIVED

WATER WELL REPORT

File 15/11E-33dc

15/11E-33dc

15/11E-28dc

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310, within 30 days from the date of well completion

NOV 19 1980

STATE OF OREGON (Please type or print)

State Well No.

State Permit No.

WATER RESOURCES DEPT

SALEM, OREGON

DESCR 3415 Sec. is 33 Per WWC 12/16/80 KRH

(1) OWNER:

Name Brad Turcott, Address 67000 Fryrear Road, Bend, OR 97701

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandon []

(3) TYPE OF WELL:

Factory [] Driven [] Jetted [] Bored []

(4) PROPOSED USE (check):

Domestic [x] Industrial [] Municipal [] Irrigation [] Test Well [] Other []

(5) CASING INSTALLED:

6" Diam. from 0 ft. to 20 ft. Gage 250, 312 ft. Gage 188

(6) PERFORATIONS:

Perforated? [x] Yes [] No. Type of perforator used factory, Size of perforations 1/8 in. by 6 in., 200 perforations from 280 ft. to 300 ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No, Manufacturer's Name, Type, Model No., Diam., Slot size, Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level, a pump test made? [] Yes [x] No, Yield: gal./min. with ft. drawdown after hrs., per test 15 gal./min. with 0 ft. drawdown after 2 hrs., Artesian flow g.p.m., Temperature of water 53 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal-Material used cement, Well sealed from land surface to 20 ft., Diameter of well bore to bottom of seal 10 in., Diameter of well bore below seal 8 in., Number of sacks of cement used in well seal 7 sacks, How was cement grout placed? pressure pump, Was a drive shoe used? [] Yes [x] No Plugs Size: location ft., Did any strata contain unusable water? [] Yes [x] No, Type of water? depth of strata, Method of sealing strata off, Was well gravel packed? [] Yes [x] No Size of gravel:, Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Deschutes Driller's well number, SW 1/4 SE 1/4 Section 28 T. 15 R. 11 E.W.M., Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 307 ft., Static level 240 ft. below land surface, Date 11-13-80, Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8, Depth drilled 312 ft. Depth of completed well 312 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include Top soil, Brown sandstone, Black sandstone, Yellow claystone, Brown lava, lost circulation, no return.

Work started 11-13 19 80 Completed 11-15 19 80, Date well drilling machine moved off of well 11-15-80 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] Bob McCoy, Date 11-15-19 80, Drilling Machine Operator's License No. 569

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name Lewis & Clark Drilling Inc., Address P.O. Box 586, Redmond, OR, [Signed] Bob McCoy, Contractor's License No. 594 Date 11-18-80