NOTICE TO WATER WELL CONTRACTOR The original and first copy	I DYDORU	3C	
of this report are to be		~- <i>II</i>	
CHARE ENGINEER CALEM ORECON 07310	A Martin N 1 Q 1Q / 4 Mart		
within 30 days from the date of well completion.	State Permit No.	eternetistennes — 15.	
of wen completion.	SALEM ORESON	-	
(1) OWNER:	(10) LOCATION OF WELL:		
Name Lue G. Farris	County Deschutes Driller's well number		
Address Star Route	S W 1/4 N, F 1/4 Section // T./55 R./2 F	W.M.	
Redmond, Oregon 97756	Bearing and distance from section or subdivision corner	· · · · · · · · · · · · · · · · · · ·	
(2) TYPE OF WORK (check):		· · · · · · · · · · · · · · · · · · ·	
New Well Deepening □ Reconditioning □ Abandon □			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found /85 ft.		
Rotary	Static level /80 ft. below land surface. Date may	¥28-7	
Dug □ Bored □ Irrigation □ Test Well □ Other □	Artesian pressure lbs. per square inch. Date		
CASING INSTALLED: Threaded □ Welded	(12) WELL LOG: Diameter of well below casing	, 11	
8" Diam. from ft. to 20 ft. Gage 277			
" Diam. fromft. toft. Gage		<u> </u>	
	Formation: Describe color, texture, grain size and structure of mand show thickness and nature of each stratum and aquifer pen	etrated,	
DEDECORATIONS.	with at least one entry for each change of formation. Report each ch position of Static Water Level and indicate principal water-bearing	ange in 1 strata.	
PERFORATIONS: Perforated? Yes No.	MATERIAL From To	SWL	
Type of perforator used	To a call		
Size of perforations in. by in.	Brown SAND STONE 3 58		
perforations fromft. toft.	CANA. 58 60	:	
perforations fromft. toft.	Hara Grax, Basalt 60 110		
	- Drugger - Transfer -	180	
(7) SCREENS: Well screen installed? Yes No	whiter Bearing Black 183 225		
Manufacturer's Name Type Model No	SANDA BrOWN Clay		
Diam. Slot size Set from ft. to ft.		.=.	
Diam. Slot size Set from ft. to			
(2) WEIT TECTS. Drawdown is amount water level is			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? ☐ Yes W No If yes, by whom?	<u> </u>		
Yield: gal./min. with ft. drawdown after hrs.		-	
" " "	e e e e e e e e e e e e e e e e e e e		
" " " " " " " " " " " " " " " " " " "			
Bailer test 20 gal./min. with 110 ft. drawdown after hrs.			
Artesian flow g.p.m.			
perature of water 57 Depth artesian flow encounteredft.	Work started Max 17 19 74 Completed May 29		
(9) CONSTRUCTION:	Date well drilling machine moved off of well May 29	1974	
Well seal-Material used Center Grouf	Drilling Machine Operator's Certification:		
Well sealed from land surface toft.	This well was constructed under my direct superv Materials used and information reported above are true		
Diameter of well bore to bottom of seal	best knowledge and belief.	n 11	
Diameter of well bore below seal	[Signed] Mulian Date May 29,	, 19.7.7	
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No		
Number of sacks of bentonite used in well seal sacks	-	* .	
Brand name of bentonite	Water Well Contractor's Certification:		
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? Yes No Plugs Size: location ft.	Name Davidson Drilling Service		
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or prin	. p . 133	
Type of water? depth of strata	Address 626 NW Pershall Way Redmond, Ore		
Method of sealing strata off	[Signed Deal Mordon Davidson		
Was well gravel packed? Yes No Size of gravel:	(Water Well Contractor)		
Gravel placed from ft. to ft.	Contractor's License No. 548 Date 6-/6	., 1924	