NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED
DEC 14 1978
WATER RESOURCES DEPT.
SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print) (Do not write above this line)

DESC 3513

State Well No. 15S/12E-11ca

State Permit No.

(1) OWNER:
Name Sam Kaser
Address 1215 N. W. Newell
Terrebonne, Ore. 97760

(2) TYPE OF WORK (check):
New Well [X] Deepening [] Reconditioning [] Abandon []
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary [X] Driven []
Cable [] Jetted []
Dug [] Bored []

(4) PROPOSED USE (check):
Domestic [X] Industrial [] Municipal []
Irrigation [] Test Well [] Other []

CASING INSTALLED:
Threaded [] Welded [X]
8 " Diam. from 2 ft. to -19 ft. Gage .250
6 " Diam. from 0 ft. to -240 ft. Gage .188
" Diam. from ft. to ft. Gage

PERFORATIONS:
Perforated? [X] Yes [] No
Type of perforator used torch
Size of perforations 1/4 in. by 12 in.
32 perforations from -220 ft. to -240 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? [] Yes [X] No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? [] Yes [X] No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 9 gal./min. with 3 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used cement
Well sealed from land surface to -19 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 8 sacks
How was cement grout placed? gravity flow
Was a drive shoe used? [] Yes [X] No Plugs Size: location ft.
Did any strata contain unusable water? [] Yes [X] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [] Yes [X] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Deschutes Driller's well number
NE 1/4 SW 1/4 Section 11 T. 15S R. 12E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 212 ft.
Static level 206 ft. below land surface. Date 12-6-78
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing 0
Depth drilled 240 ft. Depth of completed well 240 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
brown soil	0	25	
brown coarse sandstone	25	40	
grey fine sandstone	40	69	
grey hard rock	69	113	
brown hard rock	113	123	
pink fine sandstone	123	140	
brown fine sandstone	140	162	
grey coarse sandstone	162	212	206
black fine sand & gravel WB	212	240	

Work started 12-5 19 78 Completed 12-6 19 78
Date well drilling machine moved off of well 12-6 1978

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Larry K. Crawford Jr. (Drilling Machine Operator) Date 12-11 1978
Drilling Machine Operator's License No. 678

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Crawford Well Drilling, Inc. (Person, firm or corporation) (Type or print)
Address 1245 NW Lower Bridge Terrebonne, Ore.
[Signed] Larry K. Crawford (Water Well Contractor)
Contractor's License No. 570 Date 12-11, 1978

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119