NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORT

STATE OF OREGON

AUG2 3 1973 State Well No. 155/12E

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

(1) OWNER:	(10) LOCATION OF WELL:
Name Frank Neil Chase	County Deschites Driller's well number
Address Rt 1 /Box 676B Wilsonwille, Ore97070	SE % NW % Section 14 T. 15S R. 12E W.M.
Ph-638-6688	Bearing and distance from section or subdivision corner 1195 E.
(2) TYPE OF WORK (check):	& 1470' S. of the NW corner of section 14
New Well № Deepening □ Reconditioning □ Abandon □	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 9 ft.
Rotary Driven Domestic X Industrial Municipal D	7/07/77
Cable 2 Jetted	
Total III	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded \(\square\) Welded \(\sqrt{X} \)	(12) WELL LOG: Diameter of well below casingO
8" Diam. from +3 ft. to 20 ft. Gage -250	Depth drilled 43 ft. Depth of completed well 43 ft.
6 " Diam. from 0 ft. to 43 ft. Gage • 188	
ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated? X Yes I No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used torch	MATERIAL From To SWL
Size of perforations in. by 6 in.	brown sandy soil 0 2
152 perforations fromOft. to43ft.	brown course sandstone 2 9
perforations from	course sands tone & gravel
perforations from ft. to ft.	(waterbearing) 9 11
(7) SCREENS: Well screen installed? ☐ Yes ☑ No	course brown sandstone 11 21
Manufacturer's Name	black rock & tan clay
Type Model No.	(waterbearing) 21 43 16
Diam. Slot size Set from ft. to ft.	33.
Diam	
(O) TYPE I MICHAEL DOWN IN THE COMMENT OF THE COMME	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	5
Was a pump test made? ☐ Yes ☑ No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
" " " "	- Annual Control of the Control of t
11	The second secon
Bailer test 10 gal./min. with 0 ft. drawdown after 1 hrs.	4-
Section .	
herature of water 52 Depth artesian flow encounteredft.	Work started 7/14 19 73 Completed 7/23 1973
(9) CONSTRUCTION:	Date well drilling machine moved off of well 7/23 1973
Well seal—Material used cement	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision.
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief
Diameter of well bore below seal	[Signed] Lawy franchis Date 8/18 19 73
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)
Number of sacks of bentonite used in well seal	Drilling Machine Operator's License No. 678
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	∤
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? Yes No Plugs Size: location ft.	Name Crawford Well Drilling
Did any strata contain unusable water? Yes K No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address Box 17 Terrebonne Ore 97760
Method of sealing strata off	[Signed]
Was well gravel packed? 🗌 Yes 🗓 No Size of gravel:	(Water Well Contractor)
Gravel placed fromft. toft.	Contractor's License No. 451 Date 8/18 , 1973