NOTICE TO WATER WELL CONTRACTOR  The original and first copy of this report are to be filed with the DEC6 - 1971 STATE OF OREGON DESC State Well No. 15/12-15ab			
STATE ENGINEER, SALEM, OREGON 97310  within 30 days from the deperate ENGINEER  of well completion.  SALEM. OREGON 97310  State Permit No.  SALEM. OREGON 97310  SALEM. OREGON 97310			
(1) OWNER:	(10) LOCATION OF WELL:		
Name Rob BLAIR	County Deschares Driller's well number		
Address STAY PT.	N. W. 14 N. E 1/4 Section 15 T. 15 S R. 12 E W.M.		
Bedmand ore	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):	Dearing and distance from section of subdivision corner		
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	and the same of th		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	and the second control of the second control		
	Depth at which water was first found 25 ft.		
Cable Jetted   Domestic Industrial   Municipal	Static level 240 ft. below land surface. Date 12.1.71		
Dug	Artesian pressure lbs. per square inch. Date		
CASING INSTALLED: Threaded [] Welded []  "Diam. from	(12) WELL LOG: Diameter of well below casing		
ft. Gage	Depth drifted 18 1t. Depth of completed wen 1t.		
	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,		
DEDECORATIONS.	with at least one entry for each change of format position of Static Water Level and indicate prin		
PERFORATIONS: Perforated? Perforated? No.		· ·	
Type of perforator used AC7.	MATERIAL	From To SWL	
Size of perforations in. by in.	overburden	0 3	
60 perforations from 260 ft. to 280 ft.	Cong. GAAY	3 3/	
perforations from ft. to ft.	XAUA MILD	31 50	
perforations from	SANDSTONE & TONG Br.	50 16	
(7) SCREENS: Well screen installed?   Yes No	LAVA - MILA	10 11 9	
Manufacturer's Name	SANASSONO Br.	169249240	
Type Model No.	CONG. C-ray	249 254	
Diam,	Wok. Ash & E.ong.	254 282	
Diam. Slot size ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made?   Yes No If yes, by whom?	· τ		
Yield: gal./min. with ft. drawdown after hrs.			
A H		<u> </u>	
H H M M M			
Bailer test 20 gal./min. with 6 ft. drawdown after 12 hrs.			
Artesian flow g.p.m.	The state of the s		
perature of water Depth artesian flow encounteredft.	Work started //- 2.2 19 7/ Complete	ed /2 / 197/	
	Date well drilling machine moved off of well		
(9) CONSTRUCTION:		12-1 1971	
Well seal-Material used CamawT growT	Drilling Machine Operator's Certification:	dinast aumanulalan	
Well sealed from land surface toft_	This well was constructed under my Materials used and information reported		
Diameter of well bore to bottom of sealin.	best knowledge and belief.		
Diameter of well bore below seal	[Signed] 707 Carledon Date 12:2, 197].		
Number of sacks of cement used in well seal and sacks	Drilling Machine Operator's License No		
Number of sacks of bentonite used in well seal	-15		
Brand name of bentonite	Water Well Contractor's Certification:		
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is		
Was a drive shoe used? Pyes No Plugs Size: location ft.	true to the best of my knowledge and belief.		
Did any strata contain unusable water?   Yes No	Name DAU d S.O.A. D. L. L. L. N. 5 (Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address 626 N.W Parshall way, Radmondiors,		
Method of sealing strata off			
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	[Signed] (Water Well Contr	actor)	
Gravel placed from ft. to ft.	Contractor's License No. 548 Date	12-2, 1971	
	To the Holeson Control of the Contro		