## NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

EVALER WELL REPORT 69 STATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the day. of well completion.

CATE ENGINEER write above this line).

15/13-3

DULLE	11 CAL A1O.	
		/
Ctata	Permit N	
	Lemme 14	J,
***		

	T. T			
(1) OWNER: SALEM.	(11) LOCATION OF WELL:			
Name AL DENT	County DESCHUTES Driller's well	number	/	
Address RT. 1 Box 63 Radmond, One		5 R.	13 15	W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivisi	on corner		
New Well   Deepening □ Reconditioning □ Abandon □				
If abandonment, describe material and procedure in Item 12.	- ·			
(3) TYPE OF WELL: (4) PROPOSED USE (check):		· · · · · · · · · · · · · · · · · · ·	CASI	ED 70
Rotary   Driven	(12) WELL LOG: Diameter of well	below ca		
Cable   Jetted   Domestic   Industrial   Municipal   Dug   Bored   Irrigation   Test Well   Other	Depth drilled 280 ft. Depth of comp	oleted wel	1 28	O ft.
A CACTAGO TAYORATA TA	Formation: Describe color, texture, grain size			
CASING INSTALLED: Threaded Welded W	and show thickness and nature of each strat with at least one entry for each change of for			
6 "Diam. from 0 ft. to 280 ft. Gage 250	in position of Static Water Level as drilling p			
"Diam. from ft. to ft. Gage	MATERIAL	From	To	swL
" Diam. from ft. to ft. Gage	OVER BURDEN	0	弘	
PERFORATIONS: Perforated? Yes   No.	MUD GORAY LAVA	1/	16	
Type of perforator used Cutting Tokch	BLN CONGLOMER ATE	76	80	
Size of perforations /4 in. by 4 in.	MUD GLAY LAVA	80	126	
\$ 100 perforations from 260 ft. to 280 ft.	BROWN CONGLOMETATE	126	165	
perforations from ft. to ft.	MED HALD GRAS LAVE	165	190	
perforations fromft. toft.	BLACK SAND	196	240	
perforations from ft. to ft.	BRW WATER SEARING	250	255	<del></del> .
perforations from ft. to ft.	JAND	255	280	748
(7) SCREENS: Well screen installed? The Man				
(7) SCREENS: Well screen installed? ☐ Yes MNo Manufacturer's Name				
TypeModel No.	THIS WELL SERVED	<u> </u>		
Diam. Slot size Set from ft. to ft.	FROM BLACK SAND			
Diam. Slot size Set from ft. to ft.	STATA TO GROWN		<del> </del>	
(8) WATER LEVEL: Completed well.	LEVEL	<del> </del>		
Static level 248 ft. below land surface Date 4-/4-69	St. Parise			
sian pressure lbs. per square inch Date				
(9) WELL TESTS: Drawdown is amount water level is			·	
lowered below static level		-		
Was a pump test made?  Yes No If yes, by whom?	Work started 4-7 19/29 Comple	4-3 44	1-1	10/6
d: gal./min, with ft. drawdown after hrs.		tea 4-	19	196/
H H H	Date well drilling machine moved off of well	<u> </u>	15	1967
n n n n n n	Drilling Machine Operator's Certification:			
Bailer test 26 gal./min. with 4 ft. drawdown after 2 hrs.	This well was constructed under my crials used and information reported about	irect sur	ervision. rue to n	Mate- ny best
Artesian flow g.p.m. Date	knowledge and belief.			10
Temperature of water 5 2 Was a chemical analysis made?   Yes   No	[Signed] (Drilling Machine Operator)	Date 1	-16	, 19. <b>.6</b> .9
(10) CONSTRUCTION:	Drilling Machine Operator's License No.	43	88	
Well seal-Material used CEMENT GROUT	Drining Machine Operator's Encense No.		· · · · · · · · · · · · · · · · · · ·	
Depth of sealft.	Water Well Contractor's Certification:			
Diameter of well bore to bottom of seal in.	This well was drilled under my jurisdiction and this report is			
Were any loose strata cemented off? Yes No Depth	true to the best of my knowledge and belief.  NAME WOFRINER PRIVING SERVICE			
Was a drive shoe used?  Yes No	(Person, firm or corporation)	(TSP	e or print)	
Did any strata contain unusable water?   Yes No	Address Polsox 331 R	Edm	orid,	17171
Type of water? depth of strata	(D1) (VI)		<i>-</i>	
Method of sealing strata off	[Signed] (Water Well Contra	LA /	÷	
Was well gravel packed? 🗌 Yes 👿 No Size of gravel:		e i		10
Gravel placed from ft. to ft.	Contractor's License No. 497 Date	T		19. <b>k</b> .