## STATE OF OREGON

## RECEIVED

WATER WELL REPORT (as required by ORS 537.765)

JUN 1 1 1985 EASE TYPE or PRINT IN INK



(for official use only)

WATER RESOURCES DEPT			
(1) OWNER: SALEM, OREGON	(10) LOCATION OF WELL by legal description:		
Name Delbert Hupp	County Deschutes NW 4 SF 4 of Section 9 of		
Address 19774 Grade Rd.S. C.	Township, Range	lЕ, wм.	
City Silverton, OR 97381 State	1		
(2) TYPE OF WORK (check):	Tax Lot Lot Block Subdivision  MAILING ADDRESS OF WELL (or nearest address)		
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐	Manage (or well to leafest address)		
If abandonment, describe material and procedure in Item 12.			
	(11) WATER LEVEL of COMPLET	TED WELL.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):  Rotary Air Driven Domestic Dindustrial Municipal D		710	
Thermal:	Static level 282 ft. below land surface. Date 5/31/85		
Rotary Mud Dug Irrigation Withdrawal Reinjection Other:	Artesian pressure lbs. per square inch. Date		
Cable Bored Piezometric Grounding Test			
(5) CASING INSTALLED: Steel  Plastic	(12) WELL LOG: Diameter of well below casing		
Threaded 🗀 Welded 🔀	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal		
10 Diam. from 1 ft. to 19ft. Gauge 250			
ft. Gauge			
LINER INSTALLED: Steel   Plastic	water-bearing strata.		
Threaded □ Welded □	MATERIAL	From To SWL	
8 "Diam. from 0 ft. to -374 ft. Gauge .188		0 2	
(6) PERFORATIONS: Perforated? ☑ Yes ☐ No	Grey hard rock	2 78	
(6) PERFORATIONS: Perforated? \(\nabla\) Yes \(\nabla\) No Size of perforations \(\frac{1}{4}\) in. by \(\frac{1}{2}\) in.	brown coarse sandstone	78 91	
108 perforations from -314 ft. to -374 ft	grey hard rock	91 217	
	grey Hard Drokell rock	217   258	
perforations from	prowit coarse conditionerate	258 278	
perforations from ft. to f	- grey hard ruck	278 319 282	
(7) SCREENS: Well screen installed?   Yes V No	grey hard broken rock WB	319 370	
Manufacturer's Name	grey hard rock	370 374	
Type			
Diam Slot Size Set from ft. to ft.			
<u>Diam.</u> Slot Size Set from ft. to ft.			
(8) WELL TESTS:  Drawdown is amount water level is lowered below static level			
	First 125 feet drilled with	cable tool	
Was a pump test made?  Yes  No If yes, by whom?	remainder with rotary		
Yield: gal./min. with ft. drawdown after hrs	:		
Air-Land 3.0	-		
D 1			
Artesian flow g.p.m. ft. drawdown after hrs			
Temperature of water Depth artesian flow encounteredft			
(O) CONCERNACIONAL	Date work started 4/26/85 /complete	5/31/85	
(9) CONSTRUCTION: Special standards: Yes \(\sigma\) No \(\text{N}\)	Date well drilling machine moved off of well	5/31 1985	
Well seal—Material usedCement	(unbonded) Water Well Constructor Certifica		
Well sealed from land surface to	This well was constructed under my direct supe		
Diameter of well bore to bottom of seal	information reported above are true to my best known	wledge and belief.	
Diameter of well bore below sealin.		_	
Amount of sealing material sacks Depounds Depound Depound Depounds Depound	[Signed], 19,		
How was cement grout placed?	(bonded) water well Constructor Certification:		
	Bond 2206234 Issued by: Western Surety		
Was pump installed?NO	(number) (Surety Company Name)  Sn behalf of Crawford Well Drilling		
Was a drive shoe used?	(type or print page of Water Well Construction)		
Did any strata contain unusable water?		ed this ronaut is tweet to the	
Type of Water? depth of strata	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief:		
Method of sealing strata off	(Signed) Jany K		
Was well gravel packed? ☐ Yes ☐ No Size of gravel:		r)	
Gravel placed from	(Dated)		
And the second s	1		