The original and first copy of this report are to be filed with the

STATE OF OR

State	Well	No.	165	リムと	30
			/		

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

(Plea (Do not

ase type or printMAR - ! 19//		/
write above this line)	State Permit No. DEPT.	***************************************

(1) OWNER:	(10) LOCATION OF WELL:
Name Dan C. Boone / Highland Estates	County Deschutes Driller's well number
Address 2591 Northwset Way	SW 14 NE 14 Section 30 T. XXX R. 12E W.M.
Redmond, Oregon 97756	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	B data districted from Section of Subdivision Conten
New Well ☐ Deepening ☑ Reconditioning ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Donth at which water was first formal
Rotary Driven Domestic W Industrial D Municipal C	
Cable Z Jetted   Domestic Z Industrial   Municipal   Dug   Bored   Irrigation   Test Well   Other	Static level 525 ft. below land surface. Date 12/3/76
	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded □ Welded □	(12) WELL LOG: Diameter of well below casing
" Diam. from ft. to ft. Gage	Depth drilled 615 ft. Depth of completed well 615 ft.
	Formation: Describe color, texture, grain size and structure of materials;
ft. toft. Gage	and show thickness and nature of each stratum and aquifer penetrated.
PERFORATIONS: Perforated?   Yes  No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	
The state of the s	MATERIAL From To SWL
Size of perforations in. by in.  perforations from ft. to ft.	Vol. ash & Cong Gray 572 615 525
perforations from ft. to ft.	
perforations from	
(7) SCREENS: Well screen installed?   Yes   No	
Manufacturer's Name	
TypeModel No.	
Diam.       Slot size       Set from       ft. to       ft.         Diam.       Slot size       Set from       ft. to       ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	
Viola: 55 5 4	
" " "	
Bailer test gal./min. with ft drawdown after bro	
Autoria (7)	
A SPECIAL AND A	
hperature of water Depth artesian flow encountered ft.	Work started 9/20/ 19 76 Completed 12/3/ 1976
(9) CONSTRUCTION:	Date well drilling machine moved off of well 12/3/
Well seal—Material used	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision
Diameter of well bore to bottom of seal in.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal in.	[Signed] Quark M. Clip Date 2/11/, 19.77
Number of sacks of cement used in well seal sacks	
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No. 1019
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is
waterlbs./100 gals.  Was a drive shoe used? ☐ Yes ☒ No Plugs Size: locationft.	
Did any strata contain unusable water?  Yes No	Name Davidson Drilling Inc.  (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 626 N M Dental 27 M = (Type or print)
	Address 626 N. W. Pershall Way Redmond, Gre. 9775
Method of sealing strata off  Was well gravel packed?   Yes  No Size of gravel:	[Signed] Mordon Oavedson
Gravel placed from	(Water Well Contractor)  Contractor's License No. 548 Date 2/11/ 1977
	,,,,,,,,,,,,,,
(USE ADDITIONAL SH	EETS IF NECESSARY)