The original and first contract of E Water Well Report 50 state Well No. 17/11-14 6C of this report are to t filed with the MAR 1 5 1972 STATE OF OREGON STATE ENGINEER, SALEM, OREGON 97310 ENGINEER type or print) within 30 days from the date 1 ENGINEER ease type or print) State Permit No. of well completion. SALEM. OR TOWN not write above this line 440607 12/221801 (10) LOCATION OF WELL: (1) OWNER: Deschutes Driller's well number County M.R.S. Inc. Name 14 NW 14 Section 14 T.17-S R. 11E 97701 Bend, Oregon Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): Abandon 🗌 Reconditioning [Deepening [New Well If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (4) PROPOSED USE (check): Depth at which water was first found (3) TYPE OF WELL: ft. below land surface. Date2-15-7 Rotary Driven | Static level Domestic Industrial Municipal Cable Jetted 🗍 lbs. per square inch. Date Irrigation | Test Well | Other Artesian pressure Bored [CASING INSTALLED: Threaded [(12) WELL LOG: Diameter of well below casing . " Diam. from \$ 2 ft. to 174 ft. Gage .. 250 ft. Depth of completed well Depth drilled Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, .." Diam, from ft. to _____ ft. Gage with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. PERFORATIONS: Perforated? [Yes X No. MATERIAL Type of perforator used 0 20 Lava boulders Size of perforations in. by 20 70 Lava, grey, broken perforations from 70 80 Lava grey clay perforations from 130 80 Brown clay perforations from 170 Lava, grey, broken 130 (7) SCREENS: Well screen installed? 🗌 Yes 🕱 No 170 210 Brown clay 210 1320 Lava grey broken Manufacturer's Name 320 334 Type Brown clay 334 360 Diam. Slot size Set from ft. to Lava, grey 360 Diam. Slot size Set from ft. to ft. Brown clay Lava grey broken Drawdown is amount water level is lowered below static level (8) WELL TESTS: 490 420 Sediments 490 1680 Lava, grey, broken & caay Was a pump test made?
Yes You If yes, by whom? 680 Lava, grey ft. drawdown after hrs. Yield: gal./min. with Grey basalt Lava grey broken Sediments & Cinders O ft. drawdown after gal./min. with Bailer test Artesian flow g.p.m. Completed 2/20/72 Work started 10/16/71 19 perature of water 51 Depth artesian flow encountered ft. Date well drilling machine moved off of well (9) CONSTRUCTION: Grout- 4 Yds. Drilling Machine Operator's Certification: Redi-Mix Well seal-Material used . This well was constructed under my direct supervision. Well sealed from land surface to _____174 Materials used and information reported above are true to my best knowledge and belief. Diameter of well bore to bottom of seal [Signed] William Diameter of well bore below seal ... (Drilling Machine Number of sacks of cement used in well seal Drilling Machine Operator's License No. Number of sacks of bentonite used in well seal Brand name of bentonite Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name Reed's Well Drilling (Type or print) Was a drive shoe used? ★ Yes 🗆 No Plugs Size: location ft. Did any strata contain unusable water?

Yes
No 1142 Galveston Type of water? depth of strata Method of sealing strata off

Was well gravel packed?

Yes No Size of gravel: ...

Gravel placed from ft. to

ter Well Contractor)

Contractor's License No. 44.3. Date MOMMIS....., 1970