AMENDED	R	ECEIVED	109	818	
STATE OF OREGON		0947 JUL 1 4 1997	start card) # 9		0
WATER SUPPLY WELL REPORT	M441			0.312	
(as required by OKS 537.763) Instructions for completing this report are on the last page.	of this tome	R RESOURCES DE	KII. NV MEDBI UUSUI U	otion:	~
(1) OWNER: Well Number		County [] ESC AME	- Latitude		WM.
Name OMSI / TO Rad McDows Ell Address 1945 SE Water Acc.		Township 3	Al End 1/4 d	V W 1/4	`
City POSTLAND State 186	Zi#7714-3	- 040 L	Block 🔏	20001Aistou Til	200
(2) TYPE OF WORK [W New Well Deopening Alteration (repair/recondition)]	Abundorsment		(or nearest address) _5	PY LIBRET	<i>#</i>
(3) DRILL METHOD:		(10) STATIC WATER	LEVEL:		-97
Rotary Air Rotary Mud Cable Auges			w land surface. lb. per square	inch. Date	<i></i>
Other (4) PROPOSED USE:		Anesian pressure (11) WATER BEARI			
Domestic Community Industrial Info	1	Depth at which water was			
Inemai Discourage Puction.		Depth at which water was	Illst Ionia		SWL
Special Construction approval Yes No Depth of Compac	int	From	To 12.72	Estimated Flow Rate	3,42
Explosives used Yes No Type Amou		78 -			4
Diameter From To Material From To	inche or pounds		+		
114 11 30 11111114					
8 30 120		(12) WELL LOG:			
How was seal placed: Method A B	DD DE	Groun	d Elevation		
Other		Mater	ial	From To	SWL
Backfill placed from ft. to ft. Material Gravel placed from ft. to ft. Size of g	ravel	Sanay To	el 4 SANG	1 98	
(6) CASING/LINER:	Welded Threaded	W.B. SAL	wit Gravel	98 120	
7 12 195 250 KD					
Liner: 6 80 120 188 1					
Final location of shoe(s)		-			
(7) PERFORATIONS/SCREENS:					
Screens Type Mat	•				<u> </u>
From To size Number Diameter size					
100 110 813 23					
				moleted /- 4-9;	<u></u>
(8) WELLTESTS: Minimum testing time is 1 hor	ur	Date started 10	La Constructor Certific	cation:	
	Flowing Antesian	I conify that the W	ork I performed on the co	onstruction, attenuou, or a	bandonmei standards.
Pump Bailer Air Viold cal/min Drawdown Drill stem at	Time	of this well is in com Materials used and in	formation reported above	are true to the best of my	knowledge
Yield cal/min Drawdown 1//3	يطل	and belief.	80 I. W	WWC Number	· E-4
		Signed	I Constructor Certifica	tion:	
Temperature of water 45 Depth Artesian Flow	Found	I accept responsib	ility for the construction,	alteration, or abandonner	n work I work
Was a water analysis done? Yes By whom		TI Official file consumers.	with Oregon water supply the best of my knowledge:	الأهد	
Salty Muddy Odor Colored Colored	·	construction standar	10	WWC Number	755
Depth of strata:		Signed / Ad	a delen	Date_(2 <u>4</u>

JUN 1 6 1997 STATE OF OREGON IR RESOURCES DEPT. WATER SUPPLY WELL REPORT SALEM, OREGON (START CARD) # 983/3 (as required by ORS 537.765) Instructions for completing this report are on the last page of this form (9) LOCATION OF WELL by legal description: Well Number County Deschales Latitude Longitude 200126 N or S Range_ Township E or W. WM. 1/4 State Tax Lot SOO Lot Subdivision _____ (2) TYPE OF WORK New Weil Deepening Alteration (repair/recondition) Abandonment Street Address of Well (or nearest address) Street Address of Well (or nearest address) (3) DRILL METHOD: Rotary Air Rotary Mud Cable Auger ft. below land surface. Other (4) PROPOSED USE: Artesian pressure lb. per square inch. (11) WATER BEARING ZONES: ☐ Industrial Irrigation Domestic Community Other Injection Livestock Thermal (5) BORE HOLE CONSTRUCTION: Depth at which water was first found Special Construction approval Yes No Depth of Completed Well 120 ft. Estimated Flow Rate Explosives used Yes No Type Amount To <u> 30+</u> HOLE Material Diame 30 Cem, Sluro (12) WELL LOG: Method \Box B **M**C How was scal placed: Ground Elevation Other ft. Material Material From Τo SWL Backfill placed from ft. to Size of gravel Gravel placed from ft. to 44 (6) CASING/LINER: 98 120 Gauge Steel Plastic Welded Threaded Diameter 丒 Casing Liner: Final location of shoe(s) (7) PERFORATIONS/SCREENS: Method Faclar Perforations 2 Material Туре Tele/pipe Casing Liner Diameter 6-2-97 (8) WELLTESTS: Minimum testing time is 1 hour Date started Completed (unbonded) Water Well Constructor Certification: Flowing I certify that the work I performed on the construction, alteration, or abandonment Artesian Bailer 🔀 Air Pump of this well is in compliance with Oregon water supply well construction standards.

Materials used and information reported above are true to the best of my knowledge Time Yield gal/min 116 and belief. WWC Number Date Temperature of water 4/5 Depth Artesian Flow Found I accept responsibility for the construction, alteration, or abandonment work Was a water analysis done? Yes By whom performed on this well during the construction dates reported above. All work Did any strata contain water not suitable for intended use? performed during this time is in compliance with Oregon water supply well Salty Muddy Odor Colored Other construction standards. This report is true to the best of my knowledge and belief. WWC Number Depth of strata: Signed Date 6 ORIGINAL & FIRST COPY-WATER RESOURCES DEPARTMENT SECOND COPY-CONSTRUCTOR THIRD COPY-CUSTOMER

raa, niedou warei kesnnines nehairmeur okto bade

ina July

Oregon Water Resources Department


REQUEST FOR WRITTEN APPROVAL TO USE CONSTRUCTION METHODS NOT INCLUDED IN OREGON ADMINISTRATIVE RULES 690-200 THROUGH 690-240

.

Before request can be considered, the following must be answered. Requests shall be submitted to the Well Construction Specialist, Water Resources Department. Requests may also be considered by the appropriate Regional Manager.

onded Well Constructor (name, license and mailing address): Doug Aiken Aiken Well Orilling 3923 NE. 37th Redmend 71.800 Location of Well: 5W 1/4 NW 1/4 of Section 10, Township 185 Range 10E, Deschutes Co. Address at well site: Styliners Rd. Beneator Name and Address of Land Owner: OMSI 1945 SE. Water Portland, Or. 97214-3354 Name and Address of Land Owner: OMSI 1945 SE. Water Portland, Or. 97214-3354 The distance to the nearest well, septic tank or drainfield (if water supply well): 10 The unusual conditions which necessitate this request: Drilling with (System. Orilling 10 "hole for seal area and Instead hole and surface casing. Taking 10 "Casing down to hald annular open.8" for finished hole and surface casing. The proposed construction methods that the well constructor believes will be adequathis well (attach additional pages if needed) Pressure grout from -30 to 1.5., between the 8 10" Casing and removing 10" temp. Casing due of the continuous pages in the second of the continuous pages in the second of the sec	
Location of Well: SW 1/4 NW 1/4 of Section 10, Township 185 Range 10E, Deschutes Co. Address at well site: SKyLiners Rd. Bene Co. The unusual conditions of Land Owner: QM.S.I. 1945 S.E. Water Portland, Or. 97214-3354 The distance to the nearest well, septic tank or drainfield (if water supply well): 10 The unusual conditions which necessitate this request: Drilling with System. Orilling 10 hole for Seal area average for finished hole and surface casing. Taking 10" casing down to hold annular open, 8" for finished hole and surface casing. The proposed construction methods that the well constructor believes will be adequathis well (attach additional pages if needed) Pressure grout from -30 to 1.5., between the 8 10" Casing and removing 10" temp. Casing due	125
Range 10E, Deschates Co Address at well site: Skyliners Rd. Bene Start Card Number(s): 98313 Name and Address of Land Owner: OM.S.I. 1945 S.E. Water Portland, Or. 97214-3354 The distance to the nearest well, septic tank or drainfield (if water supply well): 10 The unusual conditions which necessitate this request: Dr. Iling with (System, Orilling IP hole for seal area are Taking 10" casing down to hold annular open, 8" for finished hole and surface casing. The proposed construction methods that the well constructor believes will be adequathis well (attach additional pages if needed) Pressure grout from -30' to 1.5., between the 8 10" Casing and removing 10" temp. Casing due	
Address at well site: Start Card Number(s): 98313 Name and Address of Land Owner: OM.SI 1945 S.E. Water Portland, Or. 97214-3354 The distance to the nearest well, septic tank or drainfield (if water supply well): 10 The unusual conditions which necessitate this request: Dr. 11 ing with (System, Orilling 10 hole for seal area av Taking 10 casing down to hold annular open. 8 for finished hole and surface casing. The proposed construction methods that the well constructor believes will be adequathis well (attach additional pages if needed) Pressure grout from -30 to 1.5, between the 8	
Name and Address of Land Owner: QMSI 1945 S.E. Water Portland, Or. 97214-3354 The distance to the nearest well, septic tank or drainfield (if water supply well): 10 The unusual conditions which necessitate this request: Drilling with (System, Orilling 10 "hole for seal area average for finished hole and surface casing. The proposed construction methods that the well constructor believes will be adequated this well (attach additional pages if needed) Pressure grout from -30' to 1.5., between the 8 10" Casing and removing 10" temp. Casing due	ounty.
Name and Address of Land Owner:	1, Or.
The distance to the nearest well, septic tank or drainfield (if water supply well): 10 The unusual conditions which necessitate this request: Drilling with (System, Orilling 10 "hole for seal area av Taking 10" Casing down to hold annular open, 8" for finished hole and surface casing. The proposed construction methods that the well constructor believes will be adequathis well (attach additional pages if needed) Pressure grout from -30' to 1.5., between the 8 10" Casing and removing 10" temp. Casing due	
The distance to the nearest well, septic tank or drainfield (if water supply well): 10 The unusual conditions which necessitate this request: Drilling with (System, Orilling 10 "hole for seal area av Taking 10" Casing down to hold annular open, 8" for finished hole and surface casing. The proposed construction methods that the well constructor believes will be adequathis well (attach additional pages if needed) Pressure grout from -30' to 1.5., between the 8 10" Casing and removing 10" temp. Casing due	Av
The unusual conditions which necessitate this request: Drilling with (System, Orilling 10 "hole for seal area are Taking 10" casing down to hold annular open 8" for finished hole and surface casing. The proposed construction methods that the well constructor believes will be adequated this well (attach additional pages if needed) Pressure grout from -30' to 1.5., between the 8 10" Casing and removing 10" temp. Casing due	
The unusual conditions which necessitate this request: Drilling with (System, Orilling 10 "hole for seal area, av Taking 10" casing down to hold annular open, 8" for finished hole and surface casing. The proposed construction methods that the well constructor believes will be adequated this well (attach additional pages if needed) Pressure grout from -30' to 1.5., between the 8 10" Casing and removing 10" temp. Casing due	
The unusual conditions which necessitate this request: Drilling with (System, Orilling 10 "hole for seal area, av Taking 10" casing down to hold annular open, 8" for finished hole and surface casing. The proposed construction methods that the well constructor believes will be adequated this well (attach additional pages if needed) Pressure grout from -30' to 1.5., between the 8 10" Casing and removing 10" temp. Casing due	0+'
The unusual conditions which necessitate this request: Drilling with (System. Orilling 10 "hole for seal area are Taking 10" Casing down to hold annular open. 8" for finished hole and surface casing. The proposed construction methods that the well constructor believes will be adequated this well (attach additional pages if needed) Pressure grout from -30' to 1.5., between the 8 10" Casing and removing 10" temp. Casing due	
The unusual conditions which necessitate this request: Drilling with (System, Orilling 10" hole for seal area are Taking 10" casing down to hold annular open, 8" for finished hole and surface casing. The proposed construction methods that the well constructor believes will be adequated this well (attach additional pages if needed) Pressure grout from -30' to 1.5., between the 8 10" Casing and removing 10" temp. Casing due	· · ·
Taking 10" casing down to hold annular open. 8" for finished hole and surface casing. The proposed construction methods that the well constructor believes will be adequated this well (attach additional pages if needed) Pressure grout from -30' to 1.5., between the 8. 10" Casing and removing 10" temp. Casing due	ODE
Taking 10" casing down to hold annular open 8" for finished hole and surface casing. The proposed construction methods that the well constructor believes will be adequathis well (attach additional pages if needed) Pressure grout from -30' to 1.5., between the 8 10" Casing and removing 10" temp. Casing due	
The proposed construction methods that the well constructor believes will be adequated this well (attach additional pages if needed) Pressure grout from -30' to 1.5., between the 8 10" Casing and removing 10" temp. Casing due	
The proposed construction methods that the well constructor believes will be adequated this well (attach additional pages if needed) Pressure grout from -30' to 1.5., between the 8 10" Casing and removing 10" temp. Casing due	casi
this well (attach additional pages if needed) Pressure grout from -30' to 1.5., between the 8 10" Casing and removing 10" temp. Casing due	ta for
10" Casing and removing 10" temp. Casing du	ic ioi
10" Casing and removing 10" temp. Casing du	"an
11 11	ing
I grouting process, OUEX Urills approx: 11/2 hol-	e Wi
a 10" bit. Grout will be placed by using a 2"	

(7) Diagram showing the pertinent features of the proposed well design and construction (attach additional pages if needed):



PLEASE NOTE:

- (1) If approved, all other phases of well construction must comply with the appropriate standards described in OAR 690-200 through 690-240.
- (2) If it should be determined at some future date that the well, due to its construction, is allowing groundwater contamination, waste or loss of artesian pressure, the undersigned shall return to the site and rectify the problem.
- (3) If verbal approval was granted, a written request must be submitted to the Department either within three (3) working days of the date of verbal approval or prior to the completion of the associated well work. Failure to submit a written request as described above may void prior approval.

I have read and understand the above information. I further attest that the information provided is accurate to the best of my knowledge.

Bonded Constructor Signature: Voug All	
For Water Resources Department Use Only	
Date: 6/3/97	
Approved by: Jany S. Coney Denied by:	
Remarks: Per. Phone conversation with Rob Carter	revised: 4-96

WATER RESOURCES DEPARTMENT WELL INSPECTION FORM

Owner	Name O.M.S.I. Go Rod McDowell
	Address 1945 S.E. Water Ave. Portland, OR. 97214-3354
	Purpose of Inspection Observe grouting 7.2.800
Well Location	T 18 NO R 10 BW Section 10 SWI NWZ County Deschates
	Street Address Skyliners Rd. Bend OR.
	Distance & direction from house, barn, etc.
Wall Turns	Type of well: Dylled Pro Due Dulwer Board
Well Type	Type of well: Drilled Dug Driven Bored Use of well: Domestic Stock Irrigation Industrial Municipal Test Well
	occor werr. Domestic Decek Irrigation Industrial Runicipal lest werr
Drilling	Type of drilling machine used to construct the well:
Machine	Cable tool Air rotary Mud rotary Reverse rotary
	Was the drilling machine present at the well site during the inspection: yes no
Construction Dates	Date started 6/2/97 Date completed 6/3/97
Well Contractor	Well contractor's name Aiken Well Drilling License number 1255
and Driller	Date started 6/2/97 Date completed 6/3/97 Well contractor's name Aiken Well Drilling License number 1255 Well driller's name Daug Aiken & Vince Markey License number 1255
	_
Well	Diameter of casing 7 in. Thickness of casing wall 1250 in. Diameter of drillhole 1/2/2 in.
Inspection	Maximum thickness of annular spacein. Minimum thickness of annular spacein. Casing cap or seal (describe)Welded 5feel Plate
	Describe the Meesuring Point (M.P.) Top of Casing
	M.P. is / 15 ft. (above) or below) the Land Surface Datum (LSD)
	Water Level Measurements Sounded Well Depth Sounded Open Annulus
	Tape readingft. Tape resdingft. Annulus depth30'
	M.P. (+ or -)ft. M.P. (+ or -)ft. feet below LSD
	Depth to water 44 ft. Depth of well 125 ft.
	<u>Well Seal</u> <u>Dug</u> ft. + Augered ft. + Drilled ft. = ft.
	Describe material found in seal <u>Cement grout</u>
pecial Sta	ndards Were seal samples taken: yes no _X Number of photographs taken _NO
Issued	Apparent deviation from the well construction standards None
	Appareiro de Francisco de la meri consecución seguidades
Remarks	Note: While I was observing the surface seal grouting
	Using a tire hose between the 8" and The 10" Temp.
	the 30' annular took 1/2 vards of cement grout and
	the 10" temp, casing was removed with no problems.
	THE TE TO PRODUCT OF THE PRODUCT OF
Pump	Type HP HP
Inspector	Name Vaus S. (sury) Date 6/3/97 Time of day 10:20AM
	Name / Carey Date 6/3/97 Time of day 10:20AM
	Witnesses during the inspection yes X no Name Drillers & Teff
	Address Telephone
	OFFICE USE ONLY
	Was a well log filed yes no Date the well log was filed
	Was a notice card filed yes X no Date the notice card was filed Fax 6/2/97
	Notes: