NOTICE TO WATER WELL CONTRACTOR The original and first copy

of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

(Please type or print)

STATE ENGINEER

(Do not write above this line)

ALEM. OREGON

(1) OWNER:	(10) LOCATION OF WELL:		hans
Name Gateway Cattle Co/ Paul Holsinger	CountyDeschutes Driller's well nu		·
Address Redmond, Ore 97756	E Of NE 14 Section 27 T. 17S	M	W.M.
	Bearing and distance from section or subdivisio	n corner 130	O'
(2) TYPE OF WORK (check):	south & 825' west of the NEcorner of Section		
New Well Deepening Reconditioning Abandon	27		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 630 ft.		
Rotary Driven D. Domestic Industrial Municipal	Static level 630 ft. below land surface. Date 10/16		
Cable	Artesian pressure	inch. Date	Ŧ.
CASING INSTALLED: Threaded Welded XX	(12) WELL LOG: Diameter of well be	elow casing	6
8 "Diam. from 0 ft. to 20 ft. Gage 250	Depth drilled 672 ft. Depth of completed well 672 ft.		
6	Formation: Describe color, texture, grain size a		
" Diam. fromft. Gage	and show thickness and nature of each stratum	n and aquifer pe	netrated,
DEDECORATIONS.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
i) PERFORATIONS: Perforated? Yes No.		From To	swL
Type of perforator used	MATERIAL		541
Size of perforations in. by in.	brown sandy soil	0 2	
perforations from ft. to ft.	sand & gravel	$\frac{2}{7} \mid \frac{7}{12}$	
perforations fromft, toft.	brown conglomerate	12 33	,, .
perforations fromft. toft.	gray hard rock	33 40	
(7) SCREENS: Well screen installed? ☐ Yes ₺ No	brown conglomerate	40 61	
(1) SCREENS: Well screen installed? Yes V No	gtam hard rock		
Type Model No.	brown conglomerate	61 73	—·
Diam, Slot size Set from ft. to ft.	gray broken hard rock	73 280	
Diam. Slot size Set from ft. to ft.	brown sands tone & large	280 322	
Data Landing South Control of the Co	hard boulders		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	broken gray rock no return	322 423 423 630	
Was a pump test made? Yes No If yes, by whom?	red cinder rock /strips of		
Yield: gal./min. with ft. drawdown after hrs.	brown clay and water	630 672	630
itelit. gal./iiiii. Widi it. diawdown area.			
	egan a seek seek seek seek seek seek seek se		
	- A LL LLLLL CHARACTER CONTRACTOR		
Bailer test 5 gal./min. with 0 ft. drawdown after 1 hrs.			
Artesian flow g.p.m.			
Temperature of water 64 Depth artesian flow encountered ft.	Work started 9/22 19 72 Complete	, .	19 72
(9) CONSTRUCTION:	Date well drilling machine moved off of well 1	0/16	1972
Well seal—Material usedcement	Drilling Machine Operator's Certification:	# # 1	
Well sealed from land surface to20 ft.	This well was constructed under my Materials used and information reported	above are tru	e to my
Diameter of well bore to bottom of seal in.	best knowledge and belief.	1	
Diameter of well bore below seal8 in.	[Signed] Date 1.0/19, 19.72		
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No440		
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No		
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is		
of water lbs./100 gals.	true to the best of my knowledge and belief.		
Was a drive shoe used? Yes Y No Plugs Size: location ft.	Name Crawford Well Drilling		
Did any strata contain unusable water? Yes XX No	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address Box 17 Terretonne, ore 97(60)		
Method of sealing strata off	[Signed] halo Carry Ary		
Was well gravel packed? ☐ Yes 🏗 No Size of gravel:	(Water Well Contr		
Gravel placed fromft. toft.	Contractor's License No451 Date1	0/19	, 197.