STATE OF OREGON Water Supply Well Report (as required by ORS 537.765)

DESC53193

Received Date:

Well ID Tag # L 42966

Start Card # 128830

Instructions for completing this report are on the last page of this form. (1) Owner Well Number: (9) Location of Hole by legal description Name: RON REMUND County: DESC Latitude: Township: 14.00 S Range: 11.00 E Street: PO BOX 760 Section: 17 SWSW Lot: Block: Zip Code: 97759 City: SISTERS State: OR Tax Lot: 2017 Subdivision: (2) Type of Work Street Address of Well (or nearest address): X New Alter (Recondition) Alter (Repair) MNT VIEW RD Deepening Abandonment MAP, with location identified, must be attached. (3) Drill Method (10) Static Water Level Feet below land surface: 498.0 Date: 07 / 14 / 2000 X Rotary Air Rotary Mud Cable Auger Artesian Pressure: Date: Other: (4) Proposed Use (11) Water Bearing Zones Depth at which water was first found: 590.00 ft. X Domestic | Community | Industrial | Irrigation | Injection From То est Flow swl Livestock Thermal 590.00 605.00 10.00 498 (5) Bore Hole Construction Special Standards: Depth of completed well: 605.00 ft. **Ground Elevation:** (12) Well Log Explosives Used: Amount: Type: Material From То swl Hole Seal LOAM BROKEN LAVA 0.00 3.00 Diameter From То Mtrl From То Sacks/lbs LAVA BROWN 3.00 10.00 12.00 0.00 78.00 CE 0.00 78.00 4512 LAVA GRAY FRAC LAYERS 42.00 10.00 8.00 78.00 605.00 **CINDERS RED** 42.00 51.00 **LAVA RED** 70.00 51.00 SANDSTONE 88.00 70.00 How was seal placed? Other: SAND BRN FINE GRAVELS 88.00 104.00 Back fill placed from: Material: Filter pack from: **SANDSTONE** Size: 104.00 175.00 LAVA BROWN 175.00 235.00 (6) Casing / Liner SANDSTONE CONGLOMERATE 235.00 260.00 Csng/ Shoe Shoe То **LAVA BROWN GRAY LAYERS** Liner Diameter From Gauge Mtrl Weld Thrd at used 260.00 335.00 C 8.00 2.00 78.00 .250 S X LAVA RED/CINDERS 335.00 350.00 6.00 -5.00 600.00 .188 S Х LAVA BROWN 350.00 475.00 **LAVA GRAY** 475.00 525.00 LAVA SOFT 525.00 540.00 **SANDSTONE CINDERS** 588.00 (7) Perforation / Screens 540.00 LAVA/BASALT BROKEN 588.00 605.00 498 Perforations: Csng/ Width Height #Slots Dia. t/pSize Lnr Mtrl From То Method s 585.00 605.00 0.13 3.00 216 6.00 **MACHINE** Screens: Mtrl From То S Size #Slots Dia. t/pSize Type Gauge (Minimum testing time is one hour) (8) Well Tests Date Started: 07 / 12 / 2000 Date Completed: 07 / 14 / 2000 Yield Type Units Drawdown Stem at Duration 10.00 600.00 G 1.00 (unbonded) Water Well Constructor Certification: I certify that the work I perform on the construction, alteration, or abandonment of this well is in compliance with Oregon well construction standards. Materials used and information reported above are true to the best knowledge and belief. Signed by: THOMAS R PECK W/WC #: 758 Temperature of Water: 53 F (bonded) Water Well Constructor Certification: Depth of artesian flow: Was water analysis done? l accept responsibilty for the constuction, alteration, or abandonment work performed on this well during the construction dates reported above. All work Did any strata contain water unsuitable for use? performed during this time is in compliance with Oregon well construction Too Little standards. This report is true to the best of my knowledge and belief. Odor Colored other: Signed by: **JACK ABBAS** WWC #: 1720 Depth of strata: Phone: 541-548-2787