water resources defined with the water resources defined EVE STATE of oregon within 30 days from the date.

within 30 days from the date of well completion. APR 261979 (Do not write above this line

State Well No. 185/11E-z6ac State Permit No.

No.: SOUNCES DEPT.			
1) OWNER:	(10) LOCATION OF WELL:		
Address 1275 S. F. Hwy 97	County Deschutes Driller's well number		
Address 1275 S. E. Hwy. 97	SW 14 NE 14 Section 26 T. 18	R. 11	W.M
Bend, Oregon 97701	Bearing and distance from section or subdivision		
2) TYPE OF WORK (check):			
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐			
f abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.	
3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 342 ft		
totary X Driven Domestic X Industrial Municipal		surface. Date 3	-27-79
Dug	Artesian pressure lbs. per squar		
CASING INSTALLED: Threaded Welded			
8 " Diam from +6" ft. to -19.5 ft. Gage 250	(12) WELL LOG: Diameter of well below casing 8"		
67 Diam. from0ft. to385ft. Gage188	Depth drilled 385 ft. Depth of completed well 385 ft		
"Diam from ft. to ft. Gage	Formation: Describe color, texture, grain size a		
	and show thickness and nature of each stratum and aquifer penetrated with at least one entry for each change of formation. Report each change in		
PERFORATIONS: Perforated? [X Yes] No.	position of Static Water Level and indicate prin	cipal water-bear	ing strata
Type of perforator used Factory	MATERIAL	From To	swL
Size of perforations 3 in. by 1/8 in.	Brouwn sandy soil	0 3	
120 perforations from 365 ft. to 385 ft.	_Pumice	3 9	<u> </u>
perforations from ft. to ft.	_Tan_sand_stone	9 26	
perforations from ft. to ft.	Tan rock	26 39	
7) SCREENS: Well screen installed? Yes No	Gray rock	39 85 85 210	1
Manufacturer's Name	Brown sand stone Hard brown rock	85 210 210 230	
Type Model No.	Tan sand stone	230 305	
Diam. Slot size Set from ft. to ft.	Hard brown rock	305 320	
Diam. Slot size Set from ft. to ft.	Brown sand stone	320 342	<u> </u>
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Gray lava broken	342 385	(WB)
Was a pump test made? X Yes 🗌 No If yes, by whom?	<u> </u>		
Yield: gal./min. with ft. drawdown after hrs.			
" "	- I M I TOTAL		-
и и и	1.2		-
AIR test 10 gal./min. with ft. drawdown after 1 hrs.	·.		
Artesian flow g.p.m.			1.
perature of water Depth artesian flow encountered ft.	Work started March 16, 19 79 Complete	ad March 27	19 70
(9) CONSTRUCTION:	i a company and a company	March 27,	19
Well seal—Material used Portland cement	Drilling Machine Operator's Certification:		
Well sealed from land surface to	This well was constructed under my	direct supe	rvisiōn
Diameter of well bore to bottom of seal 14 in.	Materials used and information reported best knowledge and belief,	above are tru	ie to my
Diameter of well bore below seal8 . in.	[Signed] \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		
Number of sacks of cement used in well seal sacks.	(Drilling Machine Operator) Drilling Machine Operator's License No. 934		
How was cement grout placed?	Diming Machine Operator's Literise 140.		
	Water Well Contractor's Certification:		
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? ☐ Yes [XNo Plugs, Size: location			
Did any strata contain unusable water? 🗀 Yes 🔀 No	NameLEWIS & CLARK DRILLING CO. INC. (Type or print)		
Type of water? depth of strata	Address P. O. Box 583 Redmond, Oregon 97756		
Method of sealing strata off	[Signed]		
Vas well gravel packed? [Yes X] No Size of gravel:	(Water Well Contr		
Fravel placed from	Contractor's License No. 594 Date M	larch 28,	, 197.9