NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WEIT REPORT

(Pleasa type of or 1978
(Do not write above this line) DEPT.

State Well No. 185/11E-2666
State Permit No.

VILTER IS	FROUNCES DEL II			
(1) OWNER: SALI	EM (10) ECCATION OF WELL:			
Name Deschutes Developement Co. Inc.	County Deschutes Driller's well n	umber		
Address P.O. Box 1251 Bend, Ore	NW 14 NW 14 Section 26 T. 181	S _{R.} 11	E	W.M.
	Bearing and distance from section or subdivis	ion corner		
(2) TYPE OF WORK (check):	Lot 11 & 12 Block XX Deschi	ıtes F	lver	Woods
New Well ☐ Deepening ☐X Reconditioning ☐ Abandon ☐				
If abandonment, describe material and procedure in Item 12.	- (11) WATER LEVEL: Completed w	æll.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 233 ft.			
Rotary Driven Domestic Industrial Municipal Cable	Static level 233 ft. below land	surface. I	Date	
Dug 🗌 Bored 🗋 Irrigation 🗎 Test Well 🗎 Other 🗶	Artesian pressure lbs. per square inch. Date			
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing 6 11 275 togs			
	Depth drilled 290 ft. Depth of completed well 287 ft.			
" Diam. from ft. to ft. Gage	Enmation: Describe celar tenture			
" Diam. from ft. to ft. Gage	- and show thickness and nature of each stratu	ım and ac	uifer pe	enetrated.
PERFORATIONS: Perforated?	with at least one entry for each change of forma position of Static Water Level and indicate prin	tion. Repo icipal wat	er-bearir	:hange in 1g strata.
Type of perforator used	MATERIAL	From	То	SWL
Size of perforations in. by in.	blk basalt	275	277	
perforations from ft. to ft.		1273	~~	
perforations from ft. to ft.		277	290	233
perforations fromft. toft.				
(7) SCREENS: Well screen installed? Ves No		-		
Manufacturer's Name				
Type Model No.	T and the state of			
Diam Slot size Set from ft. to ft.				
Diam Slot size Set from ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	·			
Was a pump test made? ☆Yes ☐ No If yes, by whom? ○wnor	·			
Viola 65				
ried: 05 gai./min. with 1. drawdown after 1 hrs.				
79 7 11 11 11 11 11 11 11 11 11 11 11 11 1				
A A A				
Bailer test gal./min. with ft. drawdown after hrs. Artesian flow g.p.m.				
perature of water 56 Depth artesian flow encountered ft.	7/20 79	<u> </u>	/	
	1,722 20,1000		<u>/23</u>	19 78
(9) CONSTRUCTION:	Date well drilling machine moved off of well		/23	19 78
Well seal—Material usedundistrubed	Drilling Machine Operator's Certification:			
Well sealed from land surface to ft.	This well was constructed under my Materials used and information reported	direct	super re true	vision. to my
Diameter of well bore to bottom of sealin,	best knowledge and belief.			_
Diameter of well bore below sealin. Number of sacks of cement used in well sealsacks	[Signed] (Drilling Machine Operator)	Date8/	<u> </u>	, 197.8
How was cement grout placed?	1			
Account to the state of the sta				
The state of the s	true to the best of my knowledge and bel	ction and ief.	d this re	port is
Was a drive shoe used? Yes No Plugs Size: location ft.	Johnson Well Drilling			
Did any strata contain unusable water? Yes No	(Person, firm or corporation)	(Тур		
Type of water? depth of strata	Address 3626 NW Coyner Redmon	d , Or e	<u>}</u>	
Method of sealing strata off	[Signed] John V Johnson			
Vas well gravel packed? Yes No Size of gravel:	// Civalent went contain			_
Gravel placed from ft. to ft.	Contractor's License No. 595 Date	8/21	1	. ₁₉ 78