STATE OF OREGON

WATER SUPPLY WELL REPORT

| STATE OF OREGOTY | | |
|---|--|--|
| WATER SUPPLY WELL REPORT | WELL I.D. #L 60988 | |
| (as required by ORS 537.765) | START CARD # | 3 |
| Instructions for completing this report are on the last page of this form. | | |
| (1) LAND OWNER Name ED STAWB & SONS | (9) LOCATION OF WELL by legal description: | |
| Name ED STAWS & SONS | County DE3CIT . LatitudeLongitude | |
| Address P.O. BOX 158 | Township 22 N of S Range 10 (E) or W. WM. | |
| City SILVER LAKE State OR Zip 97638 | Section 22 SE 1/4 SW 1/4 | |
| (2) TYPE OF WORK | Tax Lot 400 LotBlockSubdivision | |
| New Well Deepening Alteration (repair/recondition) Abandonment | | |
| (3) DRILL METHOD: | Street Address of Well (or pearest address) WINER HWY 31 & HWY 97 UR | PINE |
| □ Rotary Air □ Rotary Mud □ Cable Auger | (10) STATIC WATER I EVEL. | |
| □ Other | ft. below land surface. | -11-0 |
| (4) PROPOSED USE: | Artesian pressurelb. per square inch Date | |
| □ Domestic □ Community Industrial □ Irrigation | (11) WATER BEARING ZONES: | |
| ☐ Thermal ☐ Injection ☐ Livestock ☐ Other | \cdot | |
| (5) BORE HOLE CONSTRUCTION: | Depth at which water was first found | |
| Special Construction approval Yes No Depth of Completed Well ft. | From To Estimated Flow Rate | SWL |
| Explosives used Yes You Type Amount | 11' 26' 236em | - 1 |
| HOLE SEAL | · -9 - 2 9 40 7 1 (| |
| Diameter From To / Material From To / Sacks pounds | | |
| 10" 0 18 "4" HOLE 0 18 = 4 | | |
| 6" 18' 26' | | + |
| | | |
| How was seal placed: Method $\square A \square B \square C \square D \square E$ | (12) WELL LOG: | |
| MOther 3 MIN, POUR BAG | Ground Elevation | |
| Backfill placed fromft. toft. Material | Material From To | SWL |
| Gravel placed fromft. toft. Size of gravel | PUMMY 0 3' | 1 |
| (6) CASING/LINER: | 7 00. (1.1) | |
| Diameter From To Gauge Steel Plastic Welded Threaded | GRAJET & | |
| Diameter From To Gauge Steel Plastic Welded Threaded Casing: 6" 4'-2" 19.250 | SAND MIX 3' 11' | |
| | 21,100 1112 | |
| | BROWN SAND | |
| | & GRAVEZ 11' Z6' | 7' |
| Liner: 4/2" 6' 26' SDR X | 1 26 | + • |
| | | + |
| Drive Shoe used ☐ Inside ☐ Outside ☐ None | | |
| Final location of shoe(s) | | 1 |
| (7) PERFORATIONS/SCREENS: | | + |
| ☐ Perforations Method Screens Type SAWCUT Material PVC | | 1 1 |
| | RECEIVED | |
| 7 | TILOLIVED | |
| 7 10 size Number Diameter size Casing Liner 21 26 010 950 2" 42" | JAN 1 7 2003 | |
| | | |
| | WATER RESOURCES DEPT. SALEM, OREGON | + |
| | DALLIN, UNCLUN | 1 |
| | Data started C -D2 | _ |
| (8) WELL TESTS: Minimum testing time is 1 hour Flowing | Date started 1-11-03 Completed 1-11-03 | |
| Pump Bailer Air Artesian | (unbonded) Water Well Constructor Certification: | |
| Yield gal/min Drawdown Drill stem at Time | I certify that the work I performed on the construction, alteration, or abandonment of this well is in compliance with Oregon water supply well construction | |
| 23 /2' Ihr. | standards. Materials used and information reported above are true to the be | |
| | knowledge and belief. | |
| | WWC Number | |
| 470 | Signed Date | |
| | | |
| Was a water analysis done? | | |
| performed during this time is in compliance with Oregon water supply well | | |
| Salty Muddy Odor Colored Other Construction standards. This report is true to the best of my knowledge and ballet | | |
| Depth of strata: | Signed Sum Chun WWC Number 16 | 3-12 |
| | Date / -/ | |