
The original and first can of this report are to filed with the JUL 20 1971 STATE OF OREGON STATE ENGINEER, SALEM, GRECON 47810 ENGINEER (Please type or print) within 30 days from the date of well completion. SALEM. OR TO Do not write above this line)



(1) OWNER:	(10) LOCATION OF WELL:
Name B. H. FRONABARGEN	County 2.20 Driller's well number
Address P.O. BOX 1090 BEND ORE	NF 45 F 4 Section 10 T. 18 R. 12 F W.M.
(9) TWO OF WORK (1 1)	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 7/0' ft.
Rotary Driven Domestic Industrial Municipal	Static level 706 ft. below land surface. Date & 24-7
Dug	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded	
## Diam. from ft. to 18 ft. Gage 277	(12) WELL LOG: Diameter of well below casing
"Diam. fromft. toft. Gage	Depth drilled 756 ft. Depth of completed well 750 ft.
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials;
	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes 10.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in by in.	averbanden 03
perforations from ft. to ft.	Lava (Liney 3 70
perforations fromft. toft.	dava 1Red9 7085
perforations from ft. to ft.	Java Kruy 85 115
(7) SCREENS: Well screen installed? Ves No	denders Red 115 125
West Bestell Installett. Tes Mar	Land line Brown 125 236
Manufacturer's Name Model No.	Java Broken Grey 230 490
Diam. Slot size Set from ft. to ft.	Sandistone Brown 490 660
Diam. Slot size Set from ft. to ft.	Baskat BROKEN Brey, 660 718
-	water Baring 710 720
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Sandstone Brown 720 740
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	Sanda Gravel (course) 740 750
Yield: gal./min. with ft. drawdown after hrs.	Water Bearings
" " " " " " " " " " " " "	
" " " "	(Pumping 30 & P.M.)
Bailer test /0 gal./min. with 0 ft. drawdown after 2 hrs.	
Artesian flow g.p.m.	
perature of water 56 Depth artesian flow encounteredft.	Work started 2 - 18 1971 Completed 4 - 24 1971
(9) CONSTRUCTION:	Date well drilling machine moved off of well 6-24 1971
10.00	
The second discussion of the second s	Drilling Machine Operator's Certification: This well was constructed under my direct supervision.
Well sealed from land surface toft. Diameter of well bore to bottom of sealfi.	Materials used and information reported above are true to my
	best knowledge and belief.
**************************************	[Signed] Jack Marking Operator) Date 4 24 , 1971
Number of sacks of cement used in well seal sacks Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No. 116
Brand name of bentonite	#=
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my/knowledge and belief.
Was a drive shoe used? 🗌 Yes 🏿 No Plugs Size: location ft.	Name II V bl Acocon altro
Did any strata contain unusable water? Yes No	(Person, film or corporation) (Type or print)
Type of water? depth of strata	Address SOX 5
Method of sealing strata off	Isimod Ton Della 10
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 488 Date b - 24 , 1971