NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the WATER WE	
WATER RESOURCES DEPARTMENT. STATE OF	FOREGON DESC State Well No. 185/12E-3100
SALEM, OREGON 97310 (Please type) within 30 days from the date	pe or print) $\left(\frac{1}{5} \left(\frac{1}{2} \right) \right)$
	above this line)
(1) OWNER:	(10) LOCATION OF WELL:
Name OREGON HIGH DESERT MUSEUM Address P.O. BOX 5035 BEND, ORE. 97701	County DESCHUTES Driller's well number 5569
Address P.O. BOX 5035 BEND OFF. 97701	5W 1/4 SW 1/4 Section 3/ T. 185 R. 12E W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 516 ft.
Rotary X Driven D Domestic X Industrial Municipal	
C D Jetted D Donestic A Industrial D Municipal D L D Bored D Irrigation D Test Well D Other	
	Artesian pressure lbs. per square inch. Date
) CASING INSTALLED: Threaded D Welded	(12) WELL LOG: Diameter of well below casing &
8 " Diam. from + 2 ft. to 560 ft. Gage 250	Diameter of well below cashing
	Depth drilled 592 ft. Depth of completed well 592 ft.
	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
	with at least one entry for each change of formation. Report each change in
) PERFORATIONS: Perforated? Yes D No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used TORCH	MATERIAL From To SWL
Size of perforations 3/8 in. by 6 in.	SEE ATTACHED SHEET
84 perforations from 516 ft. to 532 ft.	
42 perforations from 542 ft to 550 ft	
perforations from	
(7) SCREENS: Well screen installed? Yes X No	
Manufacturer's Name	
Type Model No	
Diam Slot size Set from ft. to ft.	
Diam Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
s a pump test made? 🔲 Yes 🕱 No If yes, by whom?	AUG0 6 1980
Yield: gal./min. with ft. drawdown after hrs.	WATER RESOURCES DEPT
" " " "	SALEM, OREGON
	-ALEM, UKEGUN
" BLEW 75 GPM WITH "AIR "	
Pailer test gal./min. with ft. drawdown after hrs.	
tesian flow g.p.m.	
nperature of water Depth artesian flow encountered ft.	Work started MAY 18 19 80 Completed AUG / 19 80
(9) CONSTRUCTION:	Date well drilling machine moved off of well AUG / 1980
Well seal-Material used CEMENT GROUT	Drilling Machine Operator's Certification:
Well sealed from land surface to 30 ft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of seal in.	best knowledge and belief.
Diameter of well bore below seal	[Signed] Et avy 19 I chmal Date Aug 5, 1980
Number of sacks of cement used in well seal 2.6 sacks	(Drilling Machine Operator)
How was cement grout placed? GROUT WAS	Drilling Machine Operator's License No. 564
DUMPED THROUGH ONE INCH	
PUMPED THROUGH ONE INCH DIPE AS THE STARTER CASING	Water Well Contractor's Certification:
WAS PULLED OUT.	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? [] Yes X No Plugs Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water? 🗌 Yes 🙀 No	Name K. STERSSER DEILING ((Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 8110 SE SUNSET LANE PURTIAND OFE
Method of sealing strata off	Plo 1 1
	[Signed] Covert L. Shassey
Was well gravel packed? Yes No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 10 Date AUG 5, 1980

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119

Fcone: 771-2355

. ..

~

12=/100-3/00

R. J. Strasser Drilling Co.

8110 S. E. Sunset Lane Portland, Oregon 97206 August 4, 1980

Log of well drilled for Oregon High Desert Museum

. • 7	0 1
top soil	0 - 1
red boulders	1 - 16
black basalt	16 - 30
boulders	30 - 80
hard black basalt	80 - 154
red boulders	154 - 164
black basalt	164 - 188
red boulders	188 - 214
black basalt	214 - 290
red lava rock	290 - 346
black basalt	346 - 384
reddish brown rock	384 - 397
black basalt	397 - 454
lost circulation	454 - 488
black basalt	488 - 516
porous brown rock	516 - 532
black basalt	532 - 542
porous black basalt	542 - 550
black basalt	550 - 562
porous brown basalt	562 - 587
hard black basalt	587 - 592

RECENCED

AUGO 6 1980 WATER RESOURCES DEPT SALEM. OREGON