57147 DESC

STATE OF OREGON Water Supply Well Report (as required by ORS 537.765)

Depth of strata:

DESC

Received Date: 11-29-2005

Well ID Tag # L **79415**

Start Card #

Instructions for completing this report are on the last page of this form.		Start Card #	177251
(1) Owner Well Number:	(9) Location of Hole by le	aal descriptic	\ <i>n</i>
Name: TERRY WALKER	· · ·	-	
TRAITS. TERRI WALKER	County: DESC Latitude: Township: 15.00 S Range:	•	de: 121°28'17"
Street: 2600 DAY ROAD	· · · · · · · · · · · · · · · · · · ·	Block:	
City: GILROY State: CA Zip Code: 95020			
(2) Type of Work	Tax Lot: 2800 Subdivisi Street Address of Well (or nearest addres		
X New Alter (Recondition) Alter (Repair)	67300 GIST ROAD	5).	
Deepening Abandonment	MAP, with location identified, must be atta	ched	
		oned.	
(3) Drill Method	(10) Static Water Level Feet below land surface: 290.0	Dete: 44 / 46 / 200	-
X Rotary Air Rotary Mud Cable Auger		Date: 11 / 16 / 200	อ
Other:	Artesian Pressure:	Date:	
(4) Proposed Use	(11) Water Bearing Zones	•	
X Domestic Community Industrial Irrigation Injection	Depth at which water was first found:	330.00 ft.	
Livestock Thermal Other:	From To est Flow swl	-	
(5) Bore Hole Construction	330.00 370.00 30.00 290		
` ′			
	(12) Well Log Ground	Elevation: 316	3 ft.
Explosives Used: Amount: Type:	Material	From	To swl
Hole Seal	-		
Diameter From To Mtrl From To Sacks/lbs	SAND PUMICE	0.00	2.00
12.00 0.00 49.00 BC 0.00 49.00 38	SAND GRAVELS LAVA	2.00 38.00	38.00 73.00
8.00 49.00 370.00	BASALT CLAY SEAMS	73.00	92.00
	LAVA GRAY	92.00	102.00
Hawwara and wheed? Others BOUDED DDV	CINDERS	102.00	106.00
How was seal placed? Other: POURED DRY Back fill placed from: Material:	BASALT	106.00	115.00
Filter pack from: Size:	LAVA GRAY HARD	115.00	146.00
	CONGLOMERATE	146.00	166.00
(6) Casing / Liner	LAVA BROKEN	166.00	192.00
Csng/ Shoe Shoe Liner Diameter From To Gauge Mtrl Weld Thrd at used	CINDERS CONGLOMERATE	192.00	210.00
C 8.00 2.00 49.00 .250 S X	LAVA FRACTURED HARD	210.00	235.00
L 6.00 -10.00 370.00 .188 S X	CINDERS	235.00	250.00
	SANDSTONE	250.00	255.00
	BASALT BROKEN	255.00	275.00
(7) Perforation / Screens	LAVA FRACTURED HARD	275.00	286.00
Perforations: Csng/	CONGLOMERATE	286.00	295.00
Mtrl From To Width Height #Slots Dia. t/pSize Lnr Method	LAVA	295.00	312.00
S 350.00 370.00 0.13 3.00 228 6.00 L MACHINE	BASALT CLAY SEAMS	312.00	352.00 290
Screens: Mtrl From To S Size #Slots Dia. t/pSize Type Gauge	LAVA FRACTURED	352.00	368.00 290
Mtrl From To S Size #Slots Dia. t/pSize Type Gauge	CONGLOMERATE	368.00	370.00
(O) 14/ II T	2 YRDS SAND GROUT	10.00	33.00
(8) Well Tests (Minimum testing time is one hour)	2 1/2 YRDS SAND GROUT	40.00	250.00
Type Yield Units Drawdown Stem at Duration	Date Started: 11 / 14 / 2005	Date Completed: 11	/ 16 / 2005
A 30.00 G 370.00 1.00	(unbonded) Water Well Constructor Ce		
	I certify that the work I perform on the construction, alteration, or abandonment of this well is in compliance with Oregon well construction standards. Materials		
	used and information reported above are tr	ue to the best knowled	ge and belief.
Temperature of Water: 53 F	Signed by: THOMAS R PECK		C #: 758
Was water analysis done? Depth of artesian flow:	(bonded) Water Well Constructor Certification:		
by whom?	I accept responsibilty for the constuction, alteration, or abandonment work performed on this well during the construction dates reported above. All work		
Did any strata contain water unsuitable for use? Too Little Salty	performed during this time is in compliance standards. This report is true to the best o		
Muddy Odor Colored other:	Signed by: JACK ABBAS	, .	C#: 1720

ABBAS WELL DRILLING CO

Phone: **541-548-2787**