NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the  WATER WELL REPORT  STATE OF OREGON  STATE OF OREGON  STATE OF OREGON		
WATER RESOURCES DEPARTMENT. C STATE OF OREGON. State Well No. 205 115 - 100		
SALEM, OREGON 97310 within 30 days from the date (Please type or print) of well completion (Please type or print) (Please type or print) (Please type or print) (Please type or print)		
of well completion (Do not write a	bove unia mite)	
	VICTER RESOURCES DEPT.	
(1) OWNER:	(10) LOCATION OF WELL:	
Name HR Miller	County Deschates Driller's well number 19	
Address 5875 Gaffin Rd. Salem. OR	NW 14 SW 14 Section 7 T. 20 R. 11 C. W.M.	
9730	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):		
New Well 💆 Deepening 🗌 Reconditioning 🖺 Abandon 🖂		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	1.0	
Potomic D Dulinon D 2 2 2 2 2 3 2 3 2 3 2 3 2 3 2 3 3 3 3	Depth at which water was first found 63	
Cable	Static level 28 ft. below land surface. Date 4 12	
Dug	Artesian pressure lbs. per square inch. Date	
CASING INSTALLED: Threaded   Welded	(10) WELL LOG	
" Diam. from O ft. to 70 ft. Gage • 350	(12) WELL LOG: Diameter of well below casing Q	
" Diam. fromft. toft. Gage	Depth drilled 70 ft. Depth of completed well 70 f	
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials	
	and show thickness and nature of each stratum and aquifer penetrate with at least one entry for each change of formation. Report each change is	
PERFORATIONS: Perforated?   Yes No.	position of Static Water Level and indicate principal water-bearing strate	
Type of perforator used	MATERIAL From To SWL	
Size of perforations in, by in,	Sandy Loam 04	
perforations fromft. toft.	White cinders - 508+ 417	
perforations from ft. to ft.	Med gray + Black Sand 7 12	
perforations fromft. toft.	gray clay 12 42	
(7) SCREENS: Well screen installed? [] Yes W. No.	glay green clay 42 63	
West setzen Mistalied: 11 163 18 140	Course sand + Sine to 63 70	
Manufacturer's Name	Med. gravel with red	
Type Model No.	cinders	
Diam. Slot size Set from ft. to ft.  Diam. Slot size Set from ft. to ft.		
Set Holl It. to It.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? ☐ Yes 📉 No If yes, by whom?		
Viold:		
Barrymin. with 11. drawdown after 11. hrs.		
the same of the sa		
" " " " " " " " " " " " " " " " " " " "	Ø	
Bailer test 30 gal./min. with 5 ft. drawdown after 2 hrs.		
Artesian flow g.p.m.		
perature of water 52 Depth artesian flow encountered ft.	Work started 4 12 1978 Completed 4 12 197	
(9) CONSTRUCTION:	Date well drilling machine moved off of well 4//2 19 7	
Course		
	Drilling Machine Operator's Certification:	
Well sealed from land surface to	This well was constructed under my direct supervision Materials used and information reported above are true to my	
Diameter of well bore to bottom of sealin.	best knowledge and belief	
Number of spelve of spelve of	[Signed] Curilling Machine Operator)	
How was cement grout placed? Hix thour	Drilling Machine Operator's License No	
. •		
	Water Well Contractor's Certification:	
	This well was drilled under my jurisdiction and this report is	
Was a drive shoe used? ☐ Yes X No Plugs Size: location ft.	true to the best of my knowledge and belief.	
Did any strata contain unusable water?   Yes X No	Name BOBS. WELLDRILLING INC	
Type of water? depth of strata	(Person, firm or corporation),  Address Has alogen albeet as Lehen or On to	
Method of rooting strate are	Address Had alogon tilley Undeferror orly	
	[Signed] Laker Calkete	
Was well gravel packed? Tyes X No Size of gravel:	(Water Well Contractor)	
Gravel placed from ft. to ft.	Contractor's License No. 121 Date May 9 9 , 19 >	