The original and first copy at the solution water we water we water resources department 2 1 1978 STATE OF	M	2/5/1	0 E 1	269
SALEM, OREGON 97310 within 30 days from ATER teresources DEPT, of well completion. SALEM. OREGON (Please type (Do not write al	or print) (C 27) State Permit			
(1) OWNER:	(10) LOCATION OF WELL:			
Name Glen H. Anderson	County Deschutes Driller's well number			
Address Box 47	NE 4NW 4 Section 2 T21S R. 10E W.M.			
Joseph, Oregon 97846	Bearing and distance from section or subdivision corner			
(2) TYPE OF WORK (check):	Glenwood Acres Huntington Rd.			
New Well Deepening □ Reconditioning □ Abandon □ If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 26			ft.
Rotary Driven Domestic Industrial Municipal X			te 9_7	
Cable Jetted Irrigation Test Well Other	Static level 22 ft. below land surface. Date 9-14-78 Artesian pressure lbs. per square inch. Date			<u>. 1 = 7 0</u>
CASING INSTALLED: Threaded □ Welded 🖺	(12) WELL LOG: Diameter of well	T- 1		
6 "Diam from 0 ft to 25 ft. Gage 250), 5			
ft. to ft. Gage				ft.
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and show thickness and nature of each stra	tum and aqu	ifer pene	etrated,
PERFORATIONS: Perforated? To Yes II No.	with at least one entry for each change of form position of Static Water Level and indicate pr	nation. Report	t each cha	ange in
Type of perforator used SaW	MATERIAL			
Size of perforations \bullet 020 in. by $2\frac{1}{2}$ in.	Top Soil _	From	1 ₁	SWL
2500 perforations from 25 ft. to 45 ft.	Plumice	14	8	
perforations from ft. to ft.	Clay Loam		10	
perforations fromft, toft.	Clay & Gravel		15	,
	Sand Red Coarde			22
(7) SCREENS: Well screen installed? E Yes \(\subseteq \text{No} \)	Clay	26 2	29	
Manufacturer's Name Simpson	Sand Fine Brown	29 L	+5	
Type PlasticModel No. 160 P.S.T. Diam. 6 Slot size •02 Get from 25 ft. to 45 ft.				
Diam. Slot size Set from ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	,			
Was a pump test made? MYes DNo If yes, by whom? Driller				
vield: 20 gal./min. with 18 ft. drawdown after 24 hrs.		-		
n n		+		
n n H		+		
Bailer test gal./min. with ft. drawdown after hrs.		+		
Artesian flow g.p.m.				
perature of water Depth artesian flow encountered ft.	Work started 9-14 19 78 Comple	ted 9-1	5	19 78
(a) CONSTRUCTION.	Date well drilling machine moved off of well	9-1	15	₁₉ 78
(9) CONSTRUCTION:				
Well seal-Material usedCement Well sealed from land surface to25ft	Drilling Machine Operator's Certification This well was constructed under m		ui n anvi	ision
Diameter of well bore to bottom of seal	Materials used and information reported	above are	e true t	to my
Diameter of well bore below seal	best knowledge and belief.	79	<u> </u>	78
Number of sacks of cement used in well seal sacks	[Signed] The Hotel	Date 12-	, ·	19/
How was cement grout placed?	Drilling Machine Operator's License No.	<u>C</u>	17	,
The state of the s	Water Wall Contractor's Continue			
	Water Well Contractor's Certification:	J1_11	47. 4	
The second secon	This well was drilled under my juris true to the best of my knowledge and be	nction and	this rep	ort is
Was a drive shoe used? ☐ Yes 🏋 No Plugs Size: location ft.	Name Mike's Wall Drilling			
Did any strata contain unusable water? Yes X No	(Person, fifm or corporation) Address 84851 Proden Lane P	(Type	or print) - H축기	
Type of water? depth of strata Method of sealing strata off	Dail. Do	-casaut		<u>1,0re</u> 7401
Was well gravel packed? ☐ Yes M No Size of gravel:	[Signed] / Land Guder Well Con	tractor)	••••••	
Gravel placed from ft. to ft.	Contractor's License No620. Date			19 78

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119

NOTICE TO WATER WELL OF The original and first copy of the are to be filed with the