## WATER WELL REPORT

7398 **DESC** 

AU5 Z

State Well No.

STATE OF OREGON

PLEASE TYPE OF PRINT IN INK ALEM. OREGON

(1) OWNER:	
------------	--

High Lakes Christian Church P.O. Box 38 State City

TaPine Ore (2) TYPE OF WORK (check):

Deepening  $\square$ 

Reconditioning [ Abandon  $\square$ 

If abandonment, describe material and procedure in Item 12.

## (4) PROPOSED USE (check): (3) TYPE OF WELL:

Domestic Rotary Air [] Driven Rotary Mud 🗓 Dug Irrigation () Thermal: X Bored

New Well

☐ Municipal Industrial Other Test Well Withdrawal □ Reinjection 

> Plastic Welded

(ധ)	CASIN	G I	NSTA	LLEI		Steel Threaded		
	6" Diam	from	٦سف	ft to	26	ft	Gauge	3

1120 PVC 

INER INSTALLED:	
" Diam. from ft. to ft.	Gauge

(8) WELL TESTS:

(6) PERFORATIONS: Perforated? □ Yes \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \					
Type of perforator used					
Size of perforations	in. by	in			
	perforations from	ft. to	ft.		
			_		

	Drawdown is amount	water level is lowered
Diam	Slot Size Set from	ft. to ft
	Slot Size Set from 26	
	J	
	Homemade	
	Well screen installed? 🕱 Yes	

as a pump test m	ade? 📮 Y	Yes □ No If yes	, by whom?	Driller -	
	20	gal./min. with	ft. dra	wdown after 6	hrs.
11		"	<b>T</b>		
air test		gal./min. with	drill stem a	t ft.	hrs.
lailer test		gal./min. wit	h ft. d	rawdown after	hrs.
agian flow		g n m			

below static level

Air test	gal	gal./min. with drill stem at			It.	nrs.
Railer test		gal./min. with f		ft. drawdown after		hrs.
esian flow	g.I	o.m.				
erature of water	1,70	Depth artesia	n flow er	count	ered	ft.
(9) CONSTRUC	CTION:	Special stand	ards: Y	es 🗆	No 🛣	
Well seal—Material use						
Well sealed from land st	urface to	1.8				ft.

Diameter of well bore to bottom of seal . 10 in.
Diameter of well bore below seal
Number of sacks of cement used in well seal sacks
How was cement grout placed?
App. B
Met. C
Was pump installed? Ves Type Sub HP Depth 25 ft.

Was pump installed? yes	Type sub HP Depth .25
Was a drive shoe used? ☐ Yes 🙀	No Plugs Size: location
Did any strata contain unusable w	ater? 🗆 Yes 🖵 No
Type of Water?	depth of strata
Method of sealing strata off	

vas well gravel packeu:	∟ res	1110	Dize of graver	
Fravel placed from		ft. to	ft	
			ATER WELL CONSTRUC	TOR

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

SP*45292-690	

(10) LOCATION O	F WEL	L:			
County Deschutes	·	Driller's wel	ll number		
S W 4 N W 4 Sect	-	B T21-S	R. 70	)_E	W.M.
Tax Lot # 1870				bdivision	
Address at well location:				. =	
		,			····
(11) WATER LEVE	EL: Con	npleted v	vell.		
Depth at which water was firs	t found	26			ft.
Static level 12			land surfac	e. Date	26_83
Artesian pressure		lbs. p	er square i	nch. Date	
(12) WELL LOG:	Diamete	r of well below	v casing E	<u> </u>	
		ft. Depth o			
for each change of formation and indicate principal water- MATER	bearing str		From	То	SWL
hnorm candy ton	coil		0	2	
brown sandy top	-20-1		2	).	
clay & gravel			),	26	
black sand & cos			26	7.0	121
VIAUN DAIM C VVC	11 DO E	-avol		40	c
			1	I	I

19 19 Date well drilling machine moved off of well

(unbonded) Water Well Constructor Certification (if applicable):

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] ...... Date ...., 19

**Bonded Water Well Constructor Certification:** 

Ex. 190\_310 Issued by: American States Ins. Co.

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Gromin Well Drilling Co. 7 LaPine Ore 97739

Date ..7-27-83....., 19......

The original and first copy of this report are to be filed with the

ft.

[Signed] .