NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be WATER WEI	LL REPORT		
filed with the STATE OF STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date WATER RESOURCES (1) OWNER: Name Allen Trailer Ct. SALEM, OREGON 97310 OREGON OREGON	OREGON State Well No. State Permit N	2/s/16k="3s	
of well completion.	bove this line)		
(1) OWNER: Name Allen Trailer Ct. Address Bt 2 Roy 30	(10) LOCATION OF THE L.		
Allon Brother Gt	(10) LOCATION OF WELL:		
Name Allen Trailer Ct. Address Rt 2 Box 39	Deschutes Driller's well n	umber	
La Pine Or. 97739	N.E. 14 N.E. Section 35 Tal S	-R. IO-E W.M.	
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivis	ion corner	
New Well Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found _ 2h ft.		
Rotary Driven Domestic Domestial Municipal X	^^	surface. Date 7/8/76	
Cable			
	Artesian pressure lbs. per squa	re inch. Date	
CASING INSTALLED: Threaded □ Welded ₩	(12) WELL LOG: Diameter of well	halam andur ()	
6	Didn't below cashing		
"Diam. fromft. toft. Gage	7.0		
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and show thickness and nature of each stratu	and structure of materials;	
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of forma position of Static Water Level and indicate prin	tion. Report each change in	
Type of perforator used Saw	MATERIAL		
00.5	<u> </u>	From To SWL	
Size of perforations 025 in. by 23 in. 1200 perforations from 221 ft. to 381 ft.	Top Soil	$\begin{array}{c c} 0 & 3 & \\ \hline 3 & \overline{} & \overline{} \end{array}$	
	Plumice	1 2 1 2 1	
perforations fromft. toft.	Clay	5 8	
perforations fromft. toft.	Clay and Gravel	8 IO	
(7) SCREENS: Well screen installed? ★□ Yes □ No	Gravel (fine)	IO I5	
Manufacturer's Name	Clay and Gravel	15 24 22	
	Sand Brown (water)	24 36	
Type Simpson Plastic Model No. 160 Glass Diam. 6 Slot size •025 Set from 222 ft. to 302 ft.	Sand and Gravel (fine)	36 38 1	
Diam Slot size ft. to ft.		 	
(0) THE T MEGAG			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? K Yes □ No If yes, by whom? Driller			
Yield: I2 gal./min. with 6 ft. drawdown after 48 hrs.			
" " "			
и и и			
The second secon	A CONTROL OF THE CONT		
Bailer test gal./min. with ft. drawdown after hrs.			
Artesian flow g.p.m.			
mperature of water 46 Depth artesian flow encounteredft.	Work started 7/8 19 76 Complete	ed 7/9 1976	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	7/9 1976	
Well seal—Material usedCement	Drilling Machine Operator's Certification:		
Well sealed from land surface to	This well was constructed under my	direct supervision.	
Diameter of well bore to bottom of seal in.	Materials used and information reported best knowledge and belief.	above are true to my	
Diameter of well bore below seal6in.		Data 7/17 10.76	
Number of sacks of cement used in well seal 51 sacks	(Drilling Machine Operator)		
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No.	917	
Brand name of bentonite			
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:		
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? 🗌 Yes 🗶 No Plugs Size: location ft.			
Did any strata contain unusable water? 🔲 Yes 🏗 No	Name Mike's Well Drilling (Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address P.O. Box 613 Pleasant Hill, Or.		
Method of sealing strata off	[Signed] Will Kirchen		
Was well gravel packed? ☐ Yes ☒ No Size of gravel:	(Water Well Contr	·	
Gravel placed from ft. to ft.	Contractor's License No. 620 Date	<u> </u>	