NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

Stata	Darmit	NTA					
/					,		

(1) OWNER: WATER RESOURCES DE	(10) LOCATION OF WELL:	_						
Name Allen Riverview Tr. Ct. SALEM. OREGON	County Deschutes Driller's well nu	ımber						
Address 52731 Huntington Rd.	N.E 4N.E 4 Section 35 T. 21 S	R. 10 E W.M.						
LaPine Ore. 97739	Bearing and distance from section or subdivision							
(2) TYPE OF WORK (check):	Lazy River South Huntington	ı Rd.						
New Well 💆 Deepening 🗌 Reconditioning 🔲 Abandon 🗆								
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.						
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	29 ft.						
Rotary Driven Domestic Industrial Municipal	24	urface. Date 7/12/78						
Cable	1	• •						
	Artesian pressure Ibs. per squar	e inch. Date						
CASING INSTALLED: Threaded Welded 51	(12) WELL LOG: Diameter of well h	elow casing						
Diditi. Livili	Depth drilled 48 ft. Depth of completed well 48 ft.							
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials;							
" Diam. fromft. toft. Gage	and show thickness and nature of each stratu	m and aquifer penetrated.						
PERFORATIONS: Perforated? *Yes No.	with at least one entry for each change of format position of Static Water Level and indicate prin	ion. Report each change in cipal water-bearing strata.						
Type of perforator used Saw	MATERIAL							
Size of perforations •020 in. by 2½ in.	Top Soil	From To SWL						
2500 perforations from 28 ft. to 48 ft.	P1umice	3 5						
perforations from ft. to ft.	Clay	5 8						
perforations fromft. toft.	Clay and Gravel	8 12						
(F) CODERIG	Black Sand	12 20						
(7) SCREENS: Well screen installed? Yes \(\text{No} \) No	Clay	20 23						
Manufacturer's Name Simpson 160 PST	Clay and Bine Gravel	23 27 24						
Type Plastic Model No. 160 PSI Diam. 6 Slot size •020 Set from 28 ft. to 48 ft.	_Sand Brown	27 40						
Diam. Slot size Set from ft. to ft.	Grawel (Fine)	40 48						
It.								
(8) WELL TESTS: Drawdown is amount water level is lowered below static level								
Was a pump test made? Yes No If yes, by whom? Driller								
Yield: 30 gal./min. with 5 ft. drawdown after 8 hrs.								
" " " " " " " " " " " " " " " " " " " "		,						
ALEX - was been the more than the second of	and the second of the second o							
Antonio M								
Artesian flow g.p.m.								
perature of water Depth artesian flow encountered ft.	Work started 7/12 19 78 Complete	d 7/12 19 78						
(9) CONSTRUCTION:	Date well drilling machine moved off of well	7/12 19 78						
Well seal—Material used Cement	Drilling Machine Operator's Certification:							
Well sealed from land surface to	This well was constructed under my	direct supervision.						
Diameter of well bore to bottom of seal	Materials used and information reported above are true to my best knowledge and belief.							
Diameter of well bore below seal		10.70 10.70						
Number of sacks of cement used in well sealPumped 125 sacks	(Drilling Machine Operator)	Q17 .						
How was cement grout placed?	Drilling Machine Operator's License No	71./						
	Water Well Contractor's Certification:	n mage						
and the second s	This well was drilled under my jurisdic true to the best of my knowledge and belie	tion and this report is						
Was a drive shoe used? Tyes 2 No Plugs	Name Mike's Well Drilling							
Did any strata contain unusable water? Yes X No	(Person, firm or corporation)	(Type or print)						
Type of water? depth of strata	Address 84851 Proden Ln. Pleasant	. nill ore.						
Method of sealing strata off	[Signed] Mile Hola	~						
Vas well gravel packed? ☐ Yes ▼ No Size of gravel:	(Water Well Contra							
Gravel placed from ft. to ft.	Contractor's License No. 620 Date	7/29 , 78						