NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be

filed with the

STATE OF OREGON JUL 3 1973 State Well No.

STATE ENGINEER, SALEM, OREGON 87310 (Please type or print) TATE ENGINEE Permit No.

(Do not write above this line) ALEM OREGON within 30 days from the date of well completion. (10) LOCATION OF WELL: (1) OWNER:

Tion hard house	Decal I.C.
Name 104 Matthews	County Jeschutes Driller's well number
Address Kte 4 Boy 1436	NW 14 NW 14 Section 6 T. 21-S R. 11-E W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well 14. Deepening Reconditioning Abandon I If abandonment, describe material and procedure in Item 12.	
	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 21 ft.
Rotary Driven Domestic Mindustrial Municipal Domestic	Static level 8 ft. below land surface. Date (c/2/6/73
Dug	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded	
CASING INSTALLED: Threaded Welded Welded To Diam. from 1 ft. to 2 ft. Gage 250	(12) WELL LOG: Diameter of well below casing
	Depth drilled $2/$ ft. Depth of completed well $2/$ ft.
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials;
ft. toft. Gage	and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Brn. Sandy top Soil 0 6
perforations fromft, toft.	Bin. Sandy (course) Clay 6 10
perforations from ft. to ft.	Brn. Clay
perforations from ft. to ft.	Coarse sand (water) 21 21 8
(7) SCREENS: Well screen installed? Ves Vo	
(7) SCREENS: Well screen installed? ☐ Yes 💢 No	
Type Model No.	
Diam. Slot size Set from ft. to ft.	H 9
Diam. Slot size Set from ft. to ft.	
	Bentonite used inside & outside
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	to losion de l'an all deille
Was a pump test made? Tyes K No If yes, by whom?	of lasing during all drilling +
Yield: gal./min. with ft. drawdown after hrs.	driving of Casing.
" " " " "	231117
n n n n n n n n n n n n n n n n n n n	
	(1) (1) (1) (1) (1) (1) (1) (1) (1) (1)
Bailer test /C gal./min. with 5 ft. drawdown after / hrs.	
Artesian flow g.p.m.	
aperature of water 46 Depth artesian flow encountered ft.	Work started 6/25 1973 Completed 6/26 1973
(9) CONSTRUCTION:	Date well drilling machine moved off of well 6/26 1973
Well seal-Material used Bentonite	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision.
Diameter of well bore to bottom of seal	Materials used and information reported above are true to my best knowledge, and delief.
Diameter of well bore below seal	
Number of sacks of cement used in well seal sacks	[Signed] (Drilling Machine Operator) Date
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No. 522
Brand name of bentonite Section Bentonite	Water Well Contractoris Contract
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of water COPOY / OD lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? Yes No Plugs Size: location ft.	Name Unningham Well Drilling
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 504 104 Bend Ove
Method of sealing strata off	[Signed] W. M. Lunghan
Was well gravel packed? ☐ Yes 🐧 No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. L. Date
(USE ADDITIONAL SHEETS IF NECESSARY) SPANSOR AND	