WATER WELL REPORT

STATE OF OREGON

R	L	C	E	I	V	E	D
---	---	---	---	---	---	---	---

State Permit No.	
ny tronge	

	 1	•	1000	
מבד	pro	:OII	Dree	man to

		State Permit No.	
TER	RESOURCES	March Property Comp.	

(1) OWNER:	(10) LOCATION OF WELL:	
Name Tim D. Judd	County Deschutes Driller's wel	11
Address 50186 Collar Dr.	NE 4 SE 4 Section 35 T.22	0.13
City LaPine State Oregon	Tax Lot # Lot 2 Blk	R. J.E. W.M. A Subdivision
(2) TYPE OF WORK (check):	Address at well location WagonTrail No	
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	rell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	
Rotary Air Driven Domestic Industrial Municipal	Static level 2 ft. below l	and surface. Date 8-27-83
Rotary Mud Dug	and the second s	er square inch. Date
C N Bored		casing
(5) CASING INSTALLED: Steel Plastic		completed well 66 ft.
Threaded Welded	Formation: Describe color, texture, grain size and stri thickness and nature of each stratum and aquifer pene	ucture of materials; and show
6	for each change of formation. Report each change in	position of Static Water Level
"Diam. from	and indicate principal water-bearing strata.	
LINER INSTALLED:	MATERIAL	From To SWL
ft. toft. Gauge	Top Soil	0 2
(6) PERFORATIONS: Perforated? ▼ Yes □ No	Plumice	2 5
Type of perforator used torch	Clay	5 7
Size of perforations 1/4 in. by 6 in.	Clay and Gravel	7 12 12
	Sand	12 14
36 slots perforations from 56 ft. to 66 ft.	Clay and Gravel	14 18
perforations from ft. to ft.	Clay/hard	18 20
(7) SCREENS: Well screen installed? Yes No	Sand/fine	20 25
Manufacturer's Name	Small gravel and sand	25 40
Type Model No.	Sand and grave/fine	40 66
Diam. Slot Size Set from ft. to ft.		
Diam. Slot Size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? ▼ Yes □ No If yes, by whom? driller	•	
l: 60 gal./min. with 6 ft. drawdown after 72 hrs.		
" " "		
Air test gal./min. with drill stem at ft. hrs.	-	- ".
Bailer test gal./min. with ft. drawdown after hrs.	· 753	
Artesian flow g.p.m.		-
berature of water Depth artesian flow encountered ft.	Work started 8-27 1983 Complete	ed 8_3] 1983
(9) CONSTRUCTION: Special standards: Yes □ No □	Date well drilling machine moved off of well	8-31 1983
Well seal—Material used Cement	Drilling Machine Operator's Certification:	
Well sealed from land surface to	This well was constructed under my direct s	upervision. Materials used
Diameter of well bore to bottom of sealin.	and information reported above are true to my b	est knowledge and belief.
Diameter of well bore below seal	[Signed] (Drilling Mactine Operator)	Date .9 5, 19 8.3
Number of sacks of cement used in well seal sacks How was cement grout placed? pressure grout	Drilling Machine Operator's License No91	7
	Water Well Contractor's Certification:	
	This well was drilled under my jurisdiction	and this report is tours to
Was pump installed?	the best of my knowledge and belief.	and this report is true to
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: locationft.	Name Mike!sW.llDrillin	g
Did any strata contain unusable water? ☐ Yes X No	Address 84857 Droden To	(Type or print)
Type of Water? depth of strata	Address 84851 Proden Lane Pl	
Method of sealing strata off	[Signed] (Water Well Control	97401
Was well gravel packed? ☐ Yes ▼No Size of gravel:	Contractor's License No6.20 Date9	
Gravel placed fromft. toft.		,, ±0,,