WATER RESOURCES DEPARTMENT, DOUG STATE of	L REPORT ECEIVED IN D. 225/	/7av-37db
SALEM, OREGON 97310 within 30 days from the date of well completion. SALEM, OREGON 97310 TER RESOURCE SPANEL WILE AN	ove this line). AUG 15 1978 te Permit No	······································
(1) OWNER:	(10) LOCATION MOTOR RESOURCES DEPT.	
Dr. K. Salata	County Douglas Driller's well number	Ž
Name //34 / 1 / 34 / 5	NW 4 St 4 Section 32 T. 225, R. 7W.	W.M.
Eltiton Onroon	Bearing and distance from section or subdivision corner	***************************************
(2) TYPE OF WORK (check):	Bearing and distance from section of subdivision corner	
New Well Deepening □ Reconditioning □ Abandon □		· ·
If abandonment, describe material and procedure in Item 12.		
	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	ft.
Rotary Driven Domestic Industrial Municipal Domestic Test Well Other	Static level 8 ft. below land surface. Date	·
Oug Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date	
CASING INSTALLED: Threaded Welded Welded Welded Threaded Threaded Welded Case	(12) WELL LOG: Diameter of well below casing. Depth drilled 155 ft. Depth of completed well	
/ð Diam. from ft. to ft. Gage		
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure and show thickness and nature of each stratum and aquife	·
	with at least one entry for each change of formation. Report exposition of Static Water Level and indicate principal water-b	
PERFORATIONS: Perforated? Yes No.		
Type of perforator used		o SWL
Size of perforations in. by in.	S6// 0 /	
perforations from ft. to ft.	Clay Gellow Brown Steky 17	
perforations from ft. to ft.	C/04-13/0+ C-100 17 18	
perforations from ft. to ft.	Clay Blue Carte 18 3	-
(7) SCREENS.	Clay-Brown- Yellow 32 37	
(7) SCREENS: Well screen installed? Yes No	Clay Blue Charley 37 44	
Manufacturer's Name	Block Shale-Block tony 42 5	
Type Model No	Bock Shale Souch 57 68	
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.	Back Shale Hose 1 68 12.	<u>5 89</u>
(8) WELL TESTS: Drawdown is amount water level is lowered below static level Change		-
Was a pump test made? Yes No If yes, by whom?		
Yield: 25 gal./min. with 2 ft. drawdown after 4 hrs.		
" " "		
n n n		
Bailer test 40 gal./min. with 2 ft. drawdown after / hrs.		
	Work started June 20 19 78 Completed Uune	3 C 19 28
perature of water (Depth artesian flow encountered ft.		
(9) CONSTRUCTION:	Date well drilling machine moved off of well Uone 30 1978	
Well seal—Material used on Tour Comey	Drilling Machine Operator's Certification:	
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used, and information reported, above are true to my	
Diameter of well bore to bottom of seal	best knowledge and belief	
Diameter of well bore below seal in.	[Signed] John Moles Date 04230, 1978	
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)	
How was cement grout placed?	Drilling Machine Operator's License No. 63	***************************************
The control of the co	Water Well Contractor's Certification:	
· · · · · · · · · · · · · · · · · · ·	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.	
Was a drive shoe used? Yes 🗆 No Plugs Size: location ft.	Name Hotel Well Dullero	
Did any strata contain unusable water? Yes No	(Type o	or print)
Type of water? depth of strata	Address PSLOOX STATE	Unegan
Method of sealing strata off	100 mar hux X hosa st	9 7440
Was well gravel packed? [] Yes Y No Size of gravel:	[Signed] (Water Well Contractor)	
On the state of th	Contractor's License No 605 Date Way & 30	1025