

WATER WELL REPORT  
STATE OF OREGON

RECEIVED DOUG  
OCT 22 1980 2618

State Well No. 225/8w-5  
State Permit No. ....

WATER RESOURCES DEPT  
SALEM, OREGON

(1) OWNER:

Name Fickle Enterprises  
Address Rt. 1 W Box 358  
City Elkton, Oregon 97436 State

(2) TYPE OF WORK (check):

New Well  Deepening  Reconditioning  Abandon   
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL: (4) PROPOSED USE (check):

Rotary Air  Driven  Domestic  Industrial  Municipal   
Rotary Mud  Dug  Irrigation  Test Well  Other   
Cable  Bored  Thermal:  Withdrawal  Reinjection

(5) CASING INSTALLED: Steel  Plastic   
Threaded  Welded   
Diam. from +1 ft. to 42 ft. Gauge 2.50  
Diam. from ft. to ft. Gauge

LINER INSTALLED:

4" Diam. from 5 ft. to 120 ft. Gauge 160 PSI

(6) PERFORATIONS: Perforated?  Yes  No

Type of perforator used SAW  
Size of perforations 1/8 in. by 2 in.  
816 perforations from 25 ft. to 125 ft.  
perforations from ft. to ft.  
perforations from ft. to ft.

(7) SCREENS: Well screen installed?  Yes  No

Manufacturer's Name Model No.  
Type Diam. Slot Size Set from ft. to ft.  
Diam. Slot Size Set from ft. to ft.

WELL TESTS: Drawdown is amount water level is lowered below static level

Was a pump test made?  Yes  No If yes, by whom?  
Yield: gal./min. with ft. drawdown after hrs.

est 90 gal./min. with drill stem at 125 ft. 1 hrs.

Bailer test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m.  
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION: Special standards: Yes  No

Well seal—Material used cement  
Well sealed from land surface to 42 ft.  
Diameter of well bore to bottom of seal 10 in.  
Diameter of well bore below seal 6 in.  
Number of sacks of cement used in well seal 12 sacks  
How was cement grout placed? poured through tremie

Was pump installed? Type HP Depth ft.

Was a drive shoe used?  Yes  No Plugs Size: location ft.

Did any strata contain unusable water?  Yes  No  
Type of Water? depth of strata

Method of sealing strata off

Was well gravel packed?  Yes  No Size of gravel: ft.

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Douglas Driller's well number  
1/4 Section 5 T. 22s R. 8w W.M.  
Tax Lot # Lot Blk Subdivision  
Address at well location:

(11) WATER LEVEL: Completed well.

Depth at which water was first found 30 ft.  
Static level 30 ft. below land surface. Date 10-9-80  
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6"

Depth drilled 125 ft. Depth of completed well 125 ft.  
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Topsoil	0	2	
Brown sandy clay	2	24	
Gray sandy clay	24	30	
Brown clay	30	34	
Gravel	34	36	
Gray blue sandstone	36	125	

Work started 10-8-80 19 Completed 10-9-80 19  
Date well drilling machine moved off of well 10-9-80 19

Drilling Machine Operator's Certification:  
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.  
[Signed] Nuk Fuller (Drilling Machine Operator) Date 10-9-80  
Drilling Machine Operator's License No. 1304

Water Well Contractor's Certification:  
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.  
Name John Beck Drilling Co. (Type or print)  
Address 3711 1/2 Immigrant Rd. Pleasant Hill, Ore.  
[Signed] Casey L. Jones (Water Well Contractor)  
Contractor's License No. 259 Date 10-9-80, 19