NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON (Please type or print)

DOUG State Well No.

State Permit No.

(Do not write above this line)

| (1) OWNER: | (10) LOCATION OF WELL: |
|--|--|
| Name Brandy Bar Limited | County Douglas Driller's well number #4 |
| Address P.O. Box 936 | 6 _ 225 _ 10W |
| Roseburg. Dregon 97470 | 7.44 |
| (2) TYPE OF WORK (check): | Bearing and distance from section or subdivision corner |
| New Well ∰ Deepening ☐ Reconditioning ☐ Abandon ☐ | 222 |
| If abandonment, describe material and procedure in Item 12. | //// 57/1 57/1 |
| (3) TYPE OF WELL: (4) PROPOSED USE (check): | (11) WATER LEVEL: Completed well. |
| Rotary XX Driven D | Depth at which water was first found 50 ft |
| ble | Static level 20 ft. below land surface. Date 12-4-79 |
| Bored Irrigation Test Well Other | Artesian pressure lbs. per square inch. Date |
| CASING INSTALLED: Threaded □ Welded X | (19) WELL LOC. |
| 6 "Diam from +1 ft. to 59 ft. Gage • 250 | (12) WELL LOG: Diameter of well below casing 6" |
| " Diam. fromft. toft. Gage | Depth drilled 60 ft. Depth of completed well 60 ft |
| " Diam. from ft. to ft. Gage | Formation: Describe color, texture, grain size and structure of materials and show thickness and nature of each stratum and aquifer penetrated |
| PERFORATIONS: Perforated? Types II No. | with at least one entry for each change of formation Report each change in |
| Totalea. 2 Tes 2 Ho. | position of Static Water Level and indicate principal water-bearing strata |
| Type of perforator used torch | MATERIAL From To SWL |
| Size of perforations 4 in. by 8 in. | Sandy Loam 0 18 |
| periorations from | |
| perforations from ft. to ft. | Sand & Gravel 18 60 |
| perforations from ft. to ft. | |
| (7) SCREENS: Well screen installed? ☐ Yes ☐ No | |
| Manufacturer's Name | N 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 |
| TypeModel No. | 2 |
| Diam, Slot size Set from ft, to ft. | PREIDER |
| Diam. Slot size Set from ft. to ft. | THE CENTER OF THE PROPERTY OF |
| (8) WELL TESTS: Drawdown is amount water level is | JAN 7 10 1000 2 2 2 |
| lowered below static level | WATER |
| as a pump test made? 🔲 Yes 🖫 No If yes, by whom? | THE SOURCES DEPTION |
| gal./min. with, ft. drawdown after hrs. | Waxhimite ClienGO! |
| He was a second of the second | |
| <i>II II II II II II II II</i> | |
| atter test 200 gal./min. with 0 ft, drawdown after 1 hrs. | |
| tesian flow g.p.m. | |
| perature of water 52 Depth artesian flow encounteredft. | Work started 12-4-79 19 Completed 12-4-79 19 |
| (9) CONSTRUCTION: | Doto woll drilling machine machine and details and the second sec |
| Well goal Meterial Cement | \$2-4-17 to |
| Well seal—Material used CBIBBIL Well sealed from land surface to 25 | Drilling Machine Operator's Certification: This well was constructed under my direct supervision. |
| Diameter of well bore to bottom of sealin. | Materials used and information reported above are true to my |
| Diameter of well bore below seal 6 in. | best knowledge and haller. |
| Number of sacks of cement used in well seal 17 | [Signed] Date 1-14-80, 19 |
| How was cement grout placed? Pressure | Drilling Machine Operator's License No. 1244 |
| The state of the s | No company of the com |
| | Water Well Contractor's Certification: |
| Word of driver than any 10 May 2 | This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. |
| Was a drive shoe used? Yes No Plugs Size: location ft. | Name G.L. Meyer Well Drilling |
| Did any strata contain unusable water? Yes X No | (Person, firm or corporation) (Type or print) |
| Type of water? depth of strata | Address 6958 N. Umpqua Hwy., Roseburg, Or. |
| Method of sealing strata off | [Signed] |
| Was well gravel packed? ☐ Yes 🔀 No Size of gravel: | (Vater Well Contractor) |
| Gravel placed fromft. toft. | Contractor's License No. 714 Date 1-14-80 , 19 |