NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPORD QUG STATE OF OREGON (Please type or print) 2855

State	Well No. 20 \$ 10W-	6

(Do not write above this line)

State	Well No.	10W-6
State	Downst with the	

(1) OWNER:	(10) LOCATION OF WELL:			
Name Brandy Bar Limited				
Address P.D. Box 936	1/ Section 6 m 225 - 10W			
Roseburg, Or. 97470	The state of the s			
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner			
New Well   ☐ Deepening ☐ Reconditioning ☐ Abandon ☐				
If abandonment, describe material and procedure in Item 12.	(11) WARRED LEWING			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.			
Rotany N Dwisson D	Depth at which water was first found 50 ft.			
Cable	Static level 20 ft. below land surface. Date 12-3-79			
g 🗍 Bored 🗍 Irrigation 🗍 Test Well 🗎 Other	Artesian pressure lbs. per square inch. Date			
(5) CASING INSTALLED: Threaded □ Welded □	(12) WELL LOG: Diameter of well below sering 6			
6 " Diam. from +1 ft. to 59 ft. Gage •250	60			
" Diam. fromft. Gage	ft. Depth of completed well ft.			
	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,			
(6) PERFORATIONS: Perforated? P. Vos. C. N.	with at least one entry for each change of formation Panort and the			
z crimiated: [2] res [] No.	position of Static Water Level and indicate principal water-bearing strata.			
Size of perforations # 8	MATERIAL From To SWL			
40	Sandy Loam 0 18			
periorations fromft. toft.				
perforations fromft. toft.	Sand & Gravel 18 60			
perforations fromft. toft.				
(7) SCREENS: Well screen installed? ☐ Yes 🖔 No				
Manufacturer's Name				
Type Model No.				
Diam. Slot size Set from ft. to ft.				
Diam. Slot size Set from ft. to ft.	RECEIVED			
(8) WELL TESTS: Drawdown is amount water level is	II N. Ren. S.J. San. H. M. Sen. S.J.			
lowered below static level  Was a pump test made?   Yes No If yes, by whom?	JAN 1 8 1980			
	WATER RESOURCES DEPT			
assistant, with tit, drawdown after hrs.	SALEM, OREGON			
The state of the s	OILEUIS			
Air "				
Believ test 200 gal./min. with 0 ft. drawdown after 1 hrs.	And the second s			
tesian flow g.p.m.				
Temperature of water 52 Depth artesian flow encountered ft.	Work started 12-7 70 to 0 10 70 4 70			
(9) CONSTRUCTION:	Date well drilling machine moved off of well 12-4-79 19			
Well seal—Material used Coment	Drilling Machine Operator's Certification:			
Well sealed from land surface to 25 ft.	This well was constructed under my direct and			
Diameter of well bore to bottom of seal 10 in.	Materials used and impormation reported above are true to my best knowledge and belief			
Diameter of well bore below seal6_ in.				
Number of sacks of cement used in well seal sacks	[Signed] Date 1-14-8[] 19 (Drilling Machine Operator)			
How was cement grout placed? Pressure	Drilling Machine Operator's License No. 1244			
· · · · · · · · · · · · · · · · · · ·				
	Water Well Contractor's Certification:			
War a duine also was a Very	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Was a drive shoe used? Yes No Plugs Size: location ft.	Name G.L. Meyer Well Drilling			
Did any strata contain unusable water?   Yes No	(Person, firm or corporation) (Type or print)			
Type of water? depth of strata	Address 6958 N. Ampqua Hwy. Roseburg. Or.			
Method of sealing strata off	9. 111			
Vas well gravel packed? ☐ Yes Yoo Size of gravel:	[Signed] (Water Well Contractor)			
Fravel placed from ft. to ft.	Contractor's License No. 714 Date 1-14-80 19			
	M			