NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT. SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON (Please type or print)

(Do not write above this line)

State Well No.

State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:
Name Brandy Bar Limited	
Address P.O. Box 936	1/ Seetten 6 - 225 - 10W
Roseburg, Oregon 97470	W.M.
(2) TYPE OF WORK (check):	Rearing and distance from section or subdivision corner
New Well Deepening Reconditioning Abandon	3
If abandonment, describe material and procedure in Item 12.	(11) WADED LEWIS C
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.
Rotary D Driven D	Depth at which water was first found 29 ft
Cable	
	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded □ Welded □	(12) WELL LOG: 5"
6 " Diam. from ±1 ft. to 79 ft. Gage • 250	Diameter of well below casing
" Diam. from ft. to ft. Gage	Depth drilled 80 ft. Depth of completed well 80 ft.
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;
(6) PERFORATIONS: Performed VI Vos. 51 No.	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
Teriorateur & res No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used torch	MATERIAL From To SWL
Size of perforations 4 in. by 8 in.	Sandy loam 0 18
perforations fromft. toft.	
periorations from	Sand & Gravel 18 80
perforations from ft. to ft.	
(7) SCREENS: Well screen installed? Yes No	
Manufacturer's Name	
Type Model No.	
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	DECEMEN
Was a pump test made? ☐ Yes M No If yes, by whom?	10013 04000
f.d: gal./min. with ft. drawdown after hrs.	JAN 1-8-1990
" " The second of the second o	WATER RESOURCES DEPT!
" "	SALEM, OREGON
Air Baller test 109 gal./min. with 0 ft. drawdown after I hrs.	
i.e. a	1
stan flow g.p.m.	The state of the s
Temperature of water 52 Depth artesian flow encounteredft.	Work started 11-28-79 19 Completed 11-28-79
(9) CONSTRUCTION:	Date well drilling machine moved off of well 11-28-79 19
Well seal—Material used Coment	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my diment
Diameter of well bore to bottom of seal 10 in.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	best knowledge and helief
Number of sacks of cement used in Well seal 17	[Signed] Date 1-14-8019
How was cement grout placed?Pressure	Drilling Machine Operator's License No. 1244
The state of the s	The state of the s
	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? Yes 🗆 No Plugs Size: location ft.	
Did any strata contain unusable water? \(\subseteq\) Yes \(\subseteq\) No	Name G.L. Mayer Well Drilling (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 6958 N. Umpqua Hwy., Roseburg, Or.
Method of sealing strata off	CP IN
Was well gravel packed? ☐ Yes [XNo Size of gravel:	[Signed] Water Well Contractor)
Gravel placed fromft. toft.	77.4
The state of the s	Contractor's License No. 14 Date 1-14-80