## WATER WELL REPORT STATE OF OREGON



## RECEIVED

EP 2 1983

235/5W-15

PLEASE TYPE OWATER NESOURCES DEPT. SALEN, OREGON

(1) OWNER:	(10) LOCATION OF WELL:	
Name BLL DUNCAN - DINCAN FAMILY CORP	County Driller's well number	
Address POBox 367	14 J 14 Section 15 T. 235 R. 5	W.M.
Dity Dean State One 97435	Tax Lot # Lot Blk S	Subdivision
(2) TYPE OF WORK (check):	Address at well location:	
New Well		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	Z_// ft.
	Static level ft. below land surf	
Rotary Air X Driven	Artesian pressure lbs. per square	
☐ Bored ☐ Thermal: Withdrawal ☐ Reinjection ☐	(12) WELL LOG: Diameter of well below casing.	<u>6</u>
(5) CASING INSTALLED: Steel 🛪 Plastic 🗆	Depth drilled 260 ft. Depth of complete	
Threaded 🗆 Welded 🔀	Formation: Describe color, texture, grain size and structure of thickness and nature of each stratum and aquifer penetrated, v	
6 Diam from 1 1 ft. to 24 ft. Gauge 1250	for each change of formation. Report each change in position	
	and indicate principal water-bearing strata.	
LINER INSTALLED:	MATERIAL From	To SWL
ft. Gauge	TOPSOIL 0	2
(6) PERFORATIONS: Perforated? ☐ Yes No	A:	
Type of perforator used	Beaux Clay 2	9
Size of perforations in. by in.	PPA, X) WEATHER SANDSTONE 9	111
perforations from	LEASO WELLFICES SHASSIENCE 7	+//
perforations from	Blue (rear Sussme than 11	75
perforations from ft. to ft.	The Control of the Co	
(7) SCREENS: Well screen installed?   Yes No	BASALT 75	240
Manufacturer's Name		
Type Model No	HARD BROWN SANDSTONE 240	243
Diam. Slot Size Set from ft. to ft.	0 1/40/100	
Diam. Slot Size Set from ft. to ft. to Prawdown is amount water level is lowered	Basalt & Cooker tutt 243	260
(8) WELL TESTS:  Drawdown is amount water level is lowered below static level	-	
Wes a pump test made? ☐ Yes KNo If yes, by whom?		
d: gal./min. with ft. drawdown after hrs.		
" " "		
Air test /8 gal/min. with drill stem at 260 ft. /2 hrs.		
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.	4	
Aperature of water Depth artesian flow encountered ft.	Work started 8/10 1983 Completed &	1983
(9) CONSTRUCTION: Special standards: Yes □ No □	Date well drilling machine moved off of well	8/11/1983
Well seal—Material used Cemen F	(unbonded) Water Well Constructor Certification	ı (if applicable):
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used	
Diameter of well bore to bottom of sealin.	and information reported above are true to my best knowledge and belief.  [Signed]	
Diameter of well bore below seal		, 10
Number of sacks of cement used in well seal sacks  How was cement grout placed? Sacks  How was cement grout placed? Sacks	Bonded Water Well Constructor Certification:	
riow was centent grout placed:	Bond 5 /40-3 7 13 Issued by: /PANS /4	any Name
	This well was drilled under my jurisdiction and t	his report is true to
Was pump installed?	the best of my knowledge and belief,  Name Christenson Der ing C	n 0
Was a drive shoe used?  Yes No Plugs Size: logation ft.	(Person, firm or corporation)	(Type or print)
Did any strata contain unusable water?   Yes No	Address 33/32 Coleman Co. Ed	genc_
Type of Water? depth of strata	[Signed] Taul Christians V-K	Res
Method of sealing strata off	Water Well Constructor	9 1000
Was well gravel packed?   Yes No Size of gravel:	Date : 8	./, 19. <b>2.5</b> .
CANCEL OF PROPERTY AND ASSOCIATION OF THE PROPERTY OF THE PROP	1	