STATE OF OREGON

(1) OWNER:

Name

City

Address

Rotary Air 🐰

Rotary Mud 🗆

 Π

WATER WELL REPORT

(as required by ORS 537.765)

John Wineman

Roseburg, OR

If abandonment, describe material and procedure in Item 12.

П

..... ft. to ...

Was a pump test made?

Yes No If yes, by whom?

CASING INSTALLED: Steel

(2) TYPE OF WORK (check): Deepening

(3) TYPE OF WELL:

Driven

Dug

Rored

." Diam. from ..

..." Diam. from

.." Diam. from

(6) PERFORATIONS:

Size of perforations

(7) SCREENS:

(8) WELL TESTS:

Manufacturer's Name ..

Air test

Bailer test

Artesian flow

pperature of water

Well seal—Material used Well sealed from land surface to

(9) CONSTRUCTION:

Diameter of well bore to bottom of seal

Was a drive shoe used? X Yes No

Did any strata contain unusable water?

Diameter of well bore below seal

How was cement grout placed? ...

Amount of sealing material ..

Method of sealing strata off

Was well gravel packed?

Gravel placed from

Was pump installed?

Type of Water?

LINER INSTALLED:

219 Big Bend Rd.



Slot Size Set from ft. to

Well screen installed?

Yes X No

Slot Size Set from

gal./min. with

gal./min. with

g.p.m.

Domestic

Irrigation Other:

Piezometric

REGEIVED OCT 15 1985 265/6W-19

PLEASE TYPE of	TO PRINT IN INK SALEM, OREGON	PT (for official use only)
	(10) LOCATION OF WELL by legal	l description:
n	County Douglas 4 4	of Section 19 of
d Rd.	Township 26S , Range 6	<u>, wm.</u>
R State	1	
Y I	Tax Lot Lot Block Subdivision	
heck):	MAILING ADDRESS OF WELL (or nearest address)	
Reconditioning \square Abandon \square	LIJ DIE DOM M.	
procedure in Item 12.		
(4) PROPOSED USE (check):	(11) WATER LEVEL of COMPLET	'ED WELL:
omestic	Depth at which water was first found 25	ft.
Thermal: rigation 🖾 Withdrawal 🗆 Reinjection 🗀	Static level 18 ft. below	land surface. Date $9-24-8$
ther:	Artesian pressure lbs. per	square inch. Date
iezometric Grounding Test	(19) WELL LOCA DE CARLO	6"
ED: Steel 🖺 Plastic 🗆	(12) WELL LOG: Diameter of well below pepth drilled 85 ft. Depth of	f completed well 85 ft.
Threaded \square Welded \square	Formation: Describe color, texture, grain size and structure	
to 39 ft. Gauge .250	and nature of each stratum and aquifer penetrated, with at l	east one entry for each change of
to ft. Gauge	formation. Report each change in position of Static Wat	er Level and indicate principal
	water-bearing strata.	
D: Steel ☐ Plastic ☐ Threaded ☐ Welded ☐	MATERIAL	From To SWL
to ft. Gauge	Brown Sandy Soil	0 16
William IV. Guago III.	Sand & Gravel	16 34
Perforated? 🛛 Yes 🗌 No	Blue Claystone	34 85
in. by 6 in.		
perforations from25 ft. to34 ft.		
perforations from ft. to ft.		
perforations from ft. to ft.		
reen installed? 🗌 Yes 🗶 No		
	- '	
Set from ft. to ft.		
Set from ft. to ft.		
Drawdown is amount water level is lowered		
below static level		
No If yes, by whom?		
/min. with ft. drawdown after hrs.		
N N N		
gal./min. with drill stem at 85 ft. 1 hrs.		
· · · · · · · · · · · · · · · · · · ·		
o.m.		
Depth artesian flow encountered ft.	Date work started 9-24-85 /complete	ed 9-24-85
Special standards: Yes 🗆 No 🛭	0.01	7
ement		
25 ft.	(unbonded) Water Well Constructor Certifica	ation (if applicable):
10 in.	This well was constructed under my direct sup	ervision. Materials used and
6 .	information reported above are true to my best kno	wledge and belief.
in.	[Signed]	Date 10-10-, 19 85
pressure		III
ST VURMEY.	(bonded) Water Well Constructor Certification	
	Bond CP-28498 Issued by: North	Pacific .
		ety Company Name)
Type	On behalf of G.L. Meyer Well Dril	ter Well Constructor)
No Plugs Size: location ft.	\bigcirc $//_{\sim}$	
? Yes D. No	This well was drilled under my jurisdiction a	nd this report is true to the
depth of strata	best of my knowledge and belief:	
	(Signed)	***************************************
No Size of gravel: PCA GYAVEL	October 10 1085	or)

NOTICE TO WATER WELL CONSTRUCTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

October

(Dated)

SP*46866-690