NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

DOUG

WATER WELL REPORT
STATE OF OREGON
(Please type or print)

(Do not write above this line) 06715

RECEIVED
JUL 20 1976
WATER RESOURCES DEPT

State Well No. .....
State Permit No. 26S/6W28

(1) OWNER:
Name DON STEVENS
Address 1564 N.W. SPRAY CT.
Roseburg, ORE. 97470

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED: Threaded ☐ Welded ☐
6" Diam. from 0 ft. to 20 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS: Perforated? ☐ Yes ☒ No.
Type of perforator used —
Size of perforations — in. by — in.
— perforations from ft. to ft.
— perforations from ft. to ft.
— perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name —
Type — Model No.
Diam. — Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " "
" AIR COMPRESSOR "
Bailer test 9 gal./min. with 0 ft. drawdown after 4 hrs.
Artesian flow g.p.m. —
Temperature of water 41 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used CEMENT GROUT
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 9 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 3 sacks
Number of sacks of bentonite used in well seal — sacks
Brand name of bentonite —
Number of pounds of bentonite per 100 gallons of water — lbs./100 gals.
Was a drive shoe used? ☐ Yes ☒ No Plugs — Size: location ft.
Did any strata contain unusable water? ☐ Yes ☐ No
Type of water? — depth of strata —
Method of sealing strata off —
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from — ft. to — ft.

(10) LOCATION OF WELL:
County Douglas Driller's well number
¼ ¼ Section 28 T. 26 R. 6W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 72 ft.
Static level 58 ft. below land surface. Date
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6
Depth drilled 160 ft. Depth of completed well 160 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
OVERBURDEN, SOIL	0	3	
SOIL & CLAY, BRN	3	11	
GRANITIZED SHALE	11	160	72

Work started 7-13- 1976 Completed 7-13- 1976
Date well drilling machine moved off of well 7-14- 1976

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] [signature] Date 7-13, 1976
(Drilling Machine Operator)
Drilling Machine Operator's License No. 288

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Gullett Bros. Well Drilling
(Person, firm or corporation) (Type or print)
Address RT. 1 Myrtle Creek, ORE.
[Signed] [signature]
(Water Well Contractor)
Contractor's License No. 252 Date 7-14-, 1976

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119