

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

RECEIVED
JUL 27 1973
STATE ENGINEER
SALEM, OREGON

State Well No.

State Permit No.

DOUG

007478

ca
275/7W-33

(1) OWNER:

Name L.W. GUGEL
Address RT. 4 BOX 1109A ROSEBURG OREGON

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL: (4) PROPOSED USE (check):

Rotary ☐ Driven ☐ Domestic ☒ Industrial ☐ Municipal ☐
Cable ☒ Jetted ☐ Irrigation ☐ Test Well ☐ Other ☐
Dug ☐ Bored ☐

CASING INSTALLED: Threaded ☐ Welded ☐

NO " Diam. from CASING ft. to INSTALLED Gage
" Diam. from " ft. to " ft. Gage
" Diam. from " ft. to " ft. Gage

PERFORATIONS: Perforated? ☐ Yes ☒ No.

Type of perforator used
Size of perforations in. by in.
perforations from " ft. to " ft.
perforations from " ft. to " ft.
perforations from " ft. to " ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from " ft. to " ft.
Diam. Slot size Set from " ft. to " ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test DRY gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used CLAY
Well sealed from land surface to 110 ft.
Diameter of well bore to bottom of seal in.
Diameter of well bore below seal in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County DOUGLAS Driller's well number GUGEL#1
NR 1/4 SW 1/4 Section 33 T. 27 R. 7 W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found NONE ft.
Static level ft. below land surface. Date
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6

Depth drilled 110 ft. Depth of completed well 110 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
SOIL SANDY	0	2	
CLAY BROWN	2	12	
CLAY YELLOW	12	27	
CLAY BLUE	27	30	
CLAY STONE GRAY	30	110	DRY
FILLED WITH PUDDLED CLAY			
SUBDIVISION 3, 73-012			

Work started 6-19 1973 Completed 6-26 1973
Date well drilling machine moved off of well 6-29 1973

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Cecil M. Storey Date 6-30, 1973
(Drilling Machine Operator)

Drilling Machine Operator's License No. 23

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name CECIL M. STOREY WELL DRILLING
(Person, firm or corporation) (Type or print)

Address RT. 4 BOX 1255 ROSEBURG OREG.

[Signed] Cecil M. Storey
(Water Well Contractor)

Contractor's License No. 263 Date 6-30, 1973