

WATER WELL REPORT

STATE OF OREGON

DOUG 008001

DOUG 8001

JUN 20 1983

State Well No.

285-7W-29

WATER RESOURCES DEPT. SALEM, OREGON

State Permit No.

(1) OWNER:

Name Dennis Staley
Address 208-E Oceano Ave.
City Santa Barbara, CA State

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL: (4) PROPOSED USE (check):
Rotary Air [X] Driven [] Domestic [X] Industrial [] Municipal []
Rotary Mud [] Dug [] Irrigation [] Test Well [] Other []
Bored [] Thermal: Withdrawal [] Reinjection []

(5) CASING INSTALLED: Steel [] Threaded [X] Plastic [] Welded [X]
6" Diam. from +1 ft. to 25 ft. Gauge .250

LINER INSTALLED:
4" Diam. from +1 ft. to 105 ft. Gauge Class 160 PVC

(6) PERFORATIONS: Perforated? [] Yes [X] No
Type of perforator used
Size of perforations in. by in.

(7) SCREENS: Well screen installed? [] Yes [X] No
Manufacturer's Name
Type Model No.
Diam. Slot Size Set from ft. to ft.
Diam. Slot Size Set from ft. to ft.

WELL TESTS: Drawdown is amount water level is lowered below static level
a pump test made? [] Yes [X] No If yes, by whom?
Field: gal./min. with ft. drawdown after hrs.
30 gal./min. with drill stem at 105 ft. 1 hrs.
Soaker test gal./min. with ft. drawdown after hrs.
Artesian flow 22 g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION: Special standards: Yes [] No [X]
Well seal—Material used Cement
Well sealed from land surface to 25 ft.
Diameter of well bore to bottom of seal 9 1/2 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 6 sacks
How was cement grout placed? pressure
Was pump installed? NO Type HP Depth ft.
Was a drive shoe used? [] Yes [X] No Plugs Size: location ft.
Did any strata contain unusable water? [] Yes [X] No
Type of Water? depth of strata
Method of sealing strata off
Was well gravel packed? [] Yes [X] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Douglas Driller's well number
1/4 Section 29 T. 28S R. 7W W.M.
Tax Lot # Lot Blk Subdivision
Address at well location: 967 Tenmile Valley Loop Rd.

(11) WATER LEVEL: Completed well.

Depth at which water was first found 56 ft.
Static level 0 ft. below land surface. Date 6-14-83
Artesian pressure 18 lbs. per square inch. Date 6-14-83

(12) WELL LOG: Diameter of well below casing 6"
Depth drilled 105 ft. Depth of completed well 105 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with 4 columns: MATERIAL, From, To, SWL. Rows include Brown Clay & Sandstone, Brown Sandstone, Soft Brown Sandstone, Broken Basalt.

Work started 6-14-83 19 Completed 6-14-83 19
Date well drilling machine moved off of well 6-14-83 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] [Signature] Date 6-16-1983
(Drilling Machine Operator)

Drilling Machine Operator's License No. 1245

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name G.L. Meyer Well Drilling
(Person, firm or corporation) (Type or print)
Address 6958 N. Umpqua Hwy., Roseburg, Or.
[Signed] [Signature] (Water Well Contractor)
Contractor's License No. 714 Date 6-16-83, 19...