Doug 003612

NOTICE TO WATER WELL CONTRACTOR

The original and first copy
of this report are to be
filed with the

STATE	ENGINEER, SALEM, OREGOD
	within 30 days from the date
	of well completion.

APR 14 196 APREASE type or print)

State	Well No.	29/6W-3
State	Permit N	0

(1) OWNER: STATE ENGINEER	(11) WELL TESTS: Drawdown is amount water level some lowered below static level Casey Jones
Name State Highway Department OREGON	Was a pump test made? XYes \(\subseteq No \) If yes, by whom? Well Drilling
A 4 4 260 1 6377 - 1 1 1 1 640 1 3 1 1	Yield: 17 10 gal./min. with 6.5 ft. drawdown after 1 hrs.
outh Umpqua River Safety Rest Area-Interstate	0 10 " 7 " 2 "
(2) LOCATION OF WELL:	" 17 " 15.5 " 0
County Douglas Driller's well number	Baller test gall/illil. With 10 data and 1
W W W	
1/4 1/4 Section T. R. W.M. Bearing and distance from section or subdivision corner	
Bearing and distance from section of subdivision corner	(12) WELL LOG: Diameter of well below casing
	Depth drilled 61 ft. Depth of completed well 61 ft.
	Formation: Describe by color, character, size of material and structure, and
	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
	MATERIAL FROM TO
(3) TYPE OF WORK (check):	MATERIAL
Alternative Fil	FILL, CLAY & RIAVEL
New Well Z Deepening Reconditioning Abandon Landonment, describe material and procedure in Item 12.	Clay & Doutect
	Gravel & clay Sand gravel & clay mixed 37 45 45
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Blue gray shale 45 61
Domestic Industrial Municipal Rotary K Driven	Dide gray share
Traigetion Test Well Other Cable Jetted	
(6) CASING INSTALLED: Threaded Welded Welded	
6 ft. to	
ft. Gage ft. Gage	
(7) PERFORATIONS: Perforated? A Yes No	
Type of perforator used torch	
Size of perforations in. by A in.	
222 sig. Togorations from 34'6" ft. to 57 ft.	
perforations from ft. to ft.	
perforations fromft. toft.	
perforations from ft. to ft.	
perforations fromft. toft.	
(8) SCREENS: Well screen installed? ☐ Yes ₹ No	
Manufacturer's Name	
Type Model No.	M 7 0067
D Slot size Set from ft. to ft.	Work started 3-9 19 67 Completed ## 3-22 1967
Diam. Slot size from ft. to ft.	Date well drilling machine moved off of well 3-22-67
(9) CONSTRUCTION:	(13) PUMP:
Cement & Bentonite	Manufacturer's Name
Well seal—Material used in seal Oemer's & Bell'00111100 Depth of seal 26 ft. Was a packer used?	Type: H.P.
Diameter of well bore to bottom of seal 15 in.	
To Double	Water Well Contractor's Certification:
	on this well was drilled under my jurisdiction and this report is
Was a drive shoe used? ☐ Yes ☐ No Size of gravel: 3/4"	true to the best of my knowledge and belief.
Gravel placed from26ft. toft.	NAME Casey Jones Well Drilling Co.
Did any strata contain unusable water? Yes No	Address Rt. 2 Box 695 Creswell, Ore. 97426
Type of water? depth of strata	Address Ht. 2 Box 699 Greswell, Ole. 91420
Method of sealing strata off	Drilling Machine Operator's License No160
(10) WATER LEVELS:	Diffing machine operator & siceuse 10
` ·	[Signed] (Water Well Contractor)
Static level 26 ft. below land surface Date 3-23-67	103 3-28-67
Artesian pressure lbs. per square inch Date	Contractor's License No Date, 19
(USE ADDITIONAL)	SHEETS IF NECESSARY)