The original and fluctions CE IVF.
of this report are tipe
filed with the JUN 2 3 1971

STATE OF OREGON
OF COMMANDER OF THE ORIGINAL OF THE OR

 $008950^{\rm State~Well~No.}$

STATE OF OREGON STATE ENGINEER, SALEM, OREGOL 97310 FR (Please type or print) within 30 days from the data E ENGINEER (Please type or print) of well completions ALEM. OR CON (Do not write above this line) CiviEER (Please type or print)

State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:
Name Chesch Wilder Comos Vallos	County // Driller's well number
- Court Court of the Court of t	05 5/1
Consol 110 lb or or o	14 14 Section 20 T. 293R. 8 W.I
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well Deepening Reconditioning Abandon	4
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 50
Rotary Driven Domestic Industrial Municipal	Static level 30 - ft. below land surface. Date 6-18:
Cable Settled	7. 4.
Dug	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing
6 " Diam. from 0 ft. to 20 ft. Gage 1/1/	Diditioned of West Descriptions
"Diam, fromft. toft. Gage	Depth drilled 88.6 ft. Depth of completed well 88.6
	Formation: Describe color, texture, grain size and structure of material
Datin Holl	and show thickness and nature of each stratum and aquifer penetrate with at least one entry for each change of formation. Report each change
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strain
Type of perforator used	MATERIAL From To SWL
	face. 03
	2 2 2
perforations from ft. to ft.	1000
perforations from ft. to ft.	Horaco 13 23
perforations fromft. toft.	- Hara Cing rosee 2788
(7) SCREENS: Well screen installed? Yes You	
(7) SCREENS: Well screen installed? Wes No Manufacturer's Name	
Type Model No.	
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? Yes No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
" " "	
" " " " " " " " " " " " " " " " " " " "	
Bailer test /5 gal./www. with 50ft. drawdown after hrs.	
Artesian flow g.p.m.	
nperature of water Depth artesian flow encountered	West started to 17 107 (0 14 16 19 10)
iperature of water Depth artesian now encountered	Work started 6 - 7 19 7/ Completed 6 - 7 8 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well 6 20 - 19
Well seal-Material used Portland Cement	Drilling Machine Operator's Certification:
Well Seal-Indictial used	This well was constructed under my direct supervisio
Well sealed from land surface toft.	Materials used and information reported above are true to meet knowledge and belief.
Diameter of well bore to bottom of seal	1 V 1 / / / / / / / / / / ~
	(Drilling Machine Operator)
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 692
Number of sacks of bentonite used in well seal sacks	
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report
of waterlbs./100 gals.	true to the best of my knowledge and belief.
Was a drive shoe used? Yes No Plugs Size: location ft.	Name JOHN, T. BECK SUTHERLIN
Did any strata contain unusable water? Yes No	(Person, firm of corporation) (Type or print)
Type of water? depth of strata	Address A 2 Bot 8 900
Method of sealing strata off	[Signed] Beck
Was well gravel packed? ☐ Yes ☑ No Size of gravel:	(Water Well Contractor)
Gravel placed from	Contractor's License No 436 Date 6 267h 19