NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

DOUG 9272

DOUG 009272

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED
JUL 20 1976
WATER RESOURCES DEPT.

State Well No. .....
State Permit No. 30s/5W-19

(1) OWNER:
Name Bill Powell
Address RT. 1 Box 124
Riddle, Ore

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED: Threaded ☐ Welded ☐
6" Diam. from 0 ft. to 20 ft. Gage 250
..." Diam. from ..... ft. to ..... ft. Gage .....
..." Diam. from ..... ft. to ..... ft. Gage .....

PERFORATIONS: — Perforated? ☐ Yes ☒ No.
e of perforator used —
Size of perforations — in. by — in.
— perforations from ..... ft. to ..... ft.
— perforations from ..... ft. to ..... ft.
— perforations from ..... ft. to ..... ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name .....
Type — Model No. .....
Diam. — Slot size — Set from ..... ft. to ..... ft.
Diam. — Slot size ..... Set from ..... ft. to ..... ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☒ Yes ☐ No If yes, by whom?
ld: 7 gal./min. with 0 ft. drawdown after 4 hrs.
" " "
" " "
Bailer test gal./min. with ft. drawdown after hrs.
esian flow g.p.m.
nperature of water 41 Depth artesian flow encountered ..... ft.

(9) CONSTRUCTION:
Well seal—Material used Cement Grout
Well sealed from land surface to 19 ft.
Diameter of well bore to bottom of seal 9 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 3 sacks
Number of sacks of bentonite used in well seal — sacks
Brand name of bentonite —
Number of pounds of bentonite per 100 gallons of water ..... lbs./100 gals.
Was a drive shoe used? ☐ Yes ☒ No Plugs — Size: location ..... ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? — depth of strata —
Method of sealing strata off —
Was well gravel packed? ☐ Yes ☒ No Size of gravel: .....
Gravel placed from — ft. to — ft.

(10) LOCATION OF WELL:
County Douglas Driller's well number
¼ ¼ Section 19 T. 30S R. 5W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found ft.
Static level 60 ft. below land surface. Date 7-13-76
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing .....
Depth drilled 140 ft. Depth of completed well ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Overburden, Soil	0	1	
CAP ROCK, Shale	1	140	

Work started 7-12- 1976 Completed 7-13- 1976
Date well drilling machine moved off of well 7-13- 1976

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] John Gillett (Drilling Machine Operator) Date 7-13-, 1976.
Drilling Machine Operator's License No. 288

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Gillett Bros. Well Drilling (Person, firm or corporation) (Type or print)
Address RT. 1 Myrtle Creek, Ore.
[Signed] John Gillett (Water Well Contractor)
Contractor's License No. 252 Date 7-13-, 1976

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*46856-119