

NOTICE TO WATER WELL CONTRACTORS
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.

DOUG 8840 WATER WELL REPORT

STATE OF OREGON
RECEIVED
(Please type or print)

(Do not write above this line)

AUG 18 1978

DOUG

State Well No. 325/6W-26 db

009840

State Permit No.

(1) OWNER:

WATER RESOURCES DEPT. LOCATION OF WELL:

Name Mrs MRS Herb Webber SALEM, OREGON

Address Glendale OR

Driller's well number

NW 1/4 SE 1/4 Section 26 T. 32S R. 6W W.M.

Bearing and distance from section or subdivision corner

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☒ Cable ☐ Dug ☐ Driven ☐ Jetted ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☒ Industrial ☐ Municipal ☐ Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED:

Threaded ☐ Welded ☒

6" Diam. from 0 ft. to 23 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? ☐ Yes ☒ No.

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.

2 1/2 gals MIN DOWN OVER TOP

Ballor test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement
Well sealed from land surface to 23 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 8 sacks
How was cement grout placed? mixed poured
VI-DRA-X-EC

Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No Size of gravel:

Gravel placed from ft. to ft.

(11) WATER LEVEL: Completed well.

Depth at which water was first found 170 ft.

Static level 55 ft. below land surface. Date 7/11/78

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6"

Depth drilled 160 ft. Depth of completed well 160 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
SOIL	0	5	
CLAY yellowish	6	18	
GREENISH brown sandstone	18	40	
GREEN GRAVITE	40	160	55

Work started 7/11 1978 Completed 7/11 1978

Date well drilling machine moved off of well 7/11 1979

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Melvin B. Reed Date 7/11, 1979
(Drilling Machine Operator)

Drilling Machine Operator's License No. 908

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name ARENT WELL DRILLING
(Person, firm or corporation) (Type or print)

Address RT 1 Box 3980 Seaside OR

[Signed] Melvin B. Reed
(Water Well Contractor)

Contractor's License No. 623 Date 7-11 1978