NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

DOUG 9926

DOUG NC

WATER WELL REPORT
STATE OF OREGON
(Please type or print)

009926 (Do not write above this line)

MAY 15 1978

State Well No. 32S/6W-35

State Permit No.

(1) OWNER:
Name Allen Wells
Address Glendale Valley Rd.
Glendale, Ore.

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED: Threaded ☐ Welded ☒
6" Diam. from 0 ft. to 90 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS: Perforated? ☒ Yes ☐ No.
Type of perforator used Acetelyne Torch
Size of perforations 1/4 in. by 6 in.
80 perforations from 70 ft. to 90 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom? —
Yield: gal./min. with ft. drawdown after hrs.
Air Compressor " "
" " " "
Bailer test 38 gal./min. with 2 ft. drawdown after 4 hrs.
Artesian flow — g.p.m.
Temperature of water 47 Depth artesian flow encountered — ft.

(9) CONSTRUCTION:
Well seal—Material used Cement Grout
Well sealed from land surface to 19 ft.
Diameter of well bore to bottom of seal 9 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 4 sacks
Number of sacks of bentonite used in well seal — sacks
Brand name of bentonite —
Number of pounds of bentonite per 100 gallons of water — lbs./100 gals.
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? — depth of strata —
Method of sealing strata off —
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Douglas Driller's well number
¼ ¼ Section 35 T. 32S R. 6W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 71 ft.
Static level 41 ft. below land surface. Date 4-22-78
Artesian pressure — lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6
Depth drilled 120 ft. Depth of completed well 120 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Overburden - Soil	0	4	
Soil + Clay - Yellow	4	11	
Decomposed Granite	11	90	71
Blue Granite - Hard	90	120	41

Work started 4-18- 1978 Completed 4-22- 1978
Date well drilling machine moved off of well 4-22- 1978

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] [signature] (Drilling Machine Operator) Date 4-22-, 1978
Drilling Machine Operator's License No. 288

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Gillett Bros Well Drilling (Person, firm or corporation) (Type or print)
Address Rt. 1 Myrtle Creek
[Signed] [signature] (Water Well Contractor)
Contractor's License No. 252 Date 4-22-, 1978

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119