## NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

## WATER WELL REPORT

STATE OF OREGON

(Please type or print)

				/						
State	Well	No.	ZN/	z	2	E	 3	2	d	Ł

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

(Do not write above this line)

State	Well No.	ZN/	225	-32	. O
State	Permit N	o	•••••		

(1) OWNER:	(10) LOCATION OF WELL:
Name John Grady	County Morrow Driller's well number
Address Box 100	1/W 145 1/2 4 Section 32 T. 2 1/ R. 27 E.W.M.
Arlington, OR	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well 💆 Deepening 🗌 Reconditioning 🗎 Abandon 🗍	
If abandonment, describe material and procedure in Item 12.	(11) WATED LEVEL Completed
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.
Rotary W Driven	Depth at which water was first found 185
Cable	Static level 42 ft. below land surface. Date 4-11-7
Dug ☐ Bored ☐ Irrigation 🖫 Test Well ☐ Other ☐	Artesian pressure lbs. per square inch. Date
CASING INSTALLED:       Threaded □       Welded ★         10." Diam. from       2. ft. to       180. ft. Gage 0.250        " Diam. from       ft. to       ft. Gage        " Diam. from       ft. to       ft. Gage	(12) WELL LOG: Diameter of well below casing 10 Depth drilled 315ft. Depth of completed well 315 Formation: Describe color, texture, grain size and structure of materials and show thickness and nature of each stratum and aquifer penetrated
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of formation. Report each change is position of Static Water Level and indicate principal water-bearing strate
Type of perforator used	
Size of perforations in. by in.	0.47
perforations from ft. to ft.	Soil 0 15 Basalt. Brown Frac 15 18
perforations from	
perforations from ft. to ft.	
(7) SCREENS: Well screen installed?   Yes   No	Sandstone         165         170           Claystone         170         178
Manufacturer's Name	Basalt, Black 178 185
Type Model No.	Basalt, Red, & Brown Frac 185 215
Diam Slot size Set from ft. to ft.	
Diam Slot size Set from ft. to ft.	Basalt, Black, Hard 215 298 Basalt, Red, & Brown H20 298 315 42
(8) WELL TESTS: Drawdown is amount water level is lowered below static level Same  Was a pump test made?   Yes  No If yes, by whom?  Yield: 500 gal./min. with ft. drawdown after  hrs.	REGREGATION
" "	JUN 15 197()
" " "	V.ATER RESOURCES DEST
Bailer test gal./min. with ft. drawdown after hrs.	SALEM, OREGON
Artesian flow g.p.m.	
erature of water 62 Depth artesian flow encountered ft.	Work started A 7 70 to Complete 2 7 70
	Work started 4 = 3 = 7 9 19 Completed 4 = 11 = 7 9 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well 4-11-79 19
Well seal—Material used	Drilling Machine Operator's Certification:  This well was constructed under my direct supervision.  Materials used and information reported above are true to my best knowledge and belief  [Signed]
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	
f water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? 🛣 Yes 🗌 No Plugs Size: location ft.  Did any strata contain unusable water? 📋 Yes 🛣 No	Name C.W. Summers Well Drilling (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address Rt. # 3 Box 143 A-1/M & F OR 97862
fethod of sealing strata off	
Vas well gravel packed? ☐ Yes ☑ No Size of gravel:	[Signed] (Water Well Contractor)
Fravel placed from	5-4-79
It. W	Contractor's License No