

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON
within 30 days from the date of well completion.

RECEIVED

JUL 11 1968

WATER WELL REPORT

STATE OF OREGON

STATE ENGINEER
SALEM OREGON

(Type or print)
(Do not write above this line)

GILL 157

State Well No.

2/22-36 B

State Permit No.

(1) OWNER:

Name Bert Grieb
Address Condon Oregon

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☒ Stock

CASING INSTALLED:

Threaded ☐ Welded ☒
6" Diam. from 0 ft. to 20 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? ☐ Yes ☒ No.

Type of perforator used

Size of perforations	in. by	in.
perforations from	ft. to	ft.
perforations from	ft. to	ft.
perforations from	ft. to	ft.
perforations from	ft. to	ft.
perforations from	ft. to	ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 271 ft. below land surface Date 6/15/68
Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?

Flow: gal./min. with ft. drawdown after hrs.
Pump Lift 5 G.P.M. From 500' (4 Hrs.)

Bailer test 5 gal./min. with 119 ft. drawdown after 1 hrs.

Artesian flow g.p.m. Date

Temperature of water 54 Was a chemical analysis made? ☐ Yes ☒ No

(10) CONSTRUCTION:

Well seal—Material used Cement
Depth of seal 20 ft.
Diameter of well bore to bottom of seal 9 7/8 in.
Were any loose strata cemented off? ☐ Yes ☒ No Depth
Was a drive shoe used? ☐ Yes ☒ No
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Gilliam Driller's well number
NW 1/4 NE 1/4 Section 36 T. 28 R. 22 E W.M.

Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing 6 3/4

Depth drilled 500 ft. Depth of completed well 500 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

MATERIAL	From	To	SWL
Soil	0	1	
BASALT BROWN	1	33	
" BLACK	33	55	
" BROWN W/ SOAPSTONE	55	64	
CLAY YELLOW	64	68	
BASALT BLACK-BROWN	68	89	
FRACTURED W/ SOAPSTONE			
BASALT BLACK	89	147	
" BLACK-BROWN WITH SOAPSTONE	147	152	
WATER BEARING			
BASALT BLACK	152	187	
BASALT " BROWN FRAC.	187	209	
" BLACK	209	258	
CINDERS RED-BROWN	258	282	
BASALT FRACTURED BLACK	282	327	
BROWN (WATER BEARING)			
BASALT BLACK	327	391	
" GREY	391	495	
BASALT BROWN FRACTURED	495	500	

Work started 6/8/1968 Completed 6/18/68 19

Date well drilling machine moved off of well 6/18 1968

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Bill Rice Date 7/2, 1968
(Drilling Machine Operator)

Drilling Machine Operator's License No. 446

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME INTERVALLEY DRILLING CO.
(Person, firm or corporation) (Type or print)

Address P.O. Box

[Signed] Off E. Elmore
(Water Well Contractor)

Contractor's License No. 398 Date 7/2, 1968