RECEIVED GILL./60
EGEIVED WATER WELL REPORT AUG 14 1968 Well No. 3N / 18 - 32 D

File Original and First Copy with the STATE ENGINEER, SALEM, OREGON

STATE ENGINEER

STATE OF OREGONS State Pour No.

SALEM CREGOR	7	-
(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level	
Name CORPS OF ENGINEERS	Was a pump test made? Yes \[ \] No If yes, by whom? \[ \sum 7 RA SSE	R
Address P.O. Box 741	Yield: 340 gal./min. with 18 ft. drawdown after 48 hrs	8.
PASCO, WASH, 99301	<u>" 225 " 42.5 " 15 "</u>	_
(2) LOCATION OF WELL: SITE C	" 148 " 23 " 9 "	
County Owner's number, if any 4276	Bailer test gal./min. with ft. drawdown after hr	<u>s.</u>
NW 14 NW 14 Section 32 T. 2N R. 19E W.M.	Artesian flow g.p.m. Date	
Bearing and distance from section or subdivision corner	Temperature of water 6/ Was a chemical analysis made?   Yes N	0
	(12) WELL LOG: Diameter of well inches	撰.
A Company of the Comp	Depth drilled 273 ft. Depth of completed well 273 ft	
		_
	Formation: Describe by color, character, size of material and structure, an show thickness of aquifers and the kind and nature of the material in eac stratum penetrated, with at least one entry for each change of formation	h L
	MATERIAL FROM TO	=
CONTRACTOR (1.1)	SANDY TOP SOIL 0 2	-
(3) TYPE OF WORK (check):	SAND 2 27	_
New Well Deepening Reconditioning Abandon Reconditioning Abandon Reconditioning Abandon Reconditioning Recondit	CEMENTED GRAVEL 27 35	-
andonment, describe material and procedure in remit.	BOULDERS 35 40	_
(5) TYPE OF WELL:	SILT AND SAND 40 42	_
Comestic M Industrial   Municipal   Rotary M Driven	GRAVEL AND BOULDERS 42 51	-
rrigation Test Well   Other   Dug   Bored	SILT AND SAND 51 56	_
	BOULDERS 56 61	_
(6) CASING INSTALLED: Threaded  Welded X	LOOSE GRAVEL 61 68	
16 " Diam. from O tt. to 93.7tt. Gage 1.375	LOOSE GRAVEL AND BOULDERS 68 82	
/2." Diam. from 0 ft. to 106.3 ft. Gage 3.75	BROKEN ROCK AND CLAY 82 97	
	BLACK AMSALT 97 104	<u>F</u>
	SOFT GREY BASALT 104 107	<del>,</del>
(7) PERFORATIONS: Perforated?   Yes No	BROKEN BROWN BASALT 107 128	>
Type of perforator used	HARD GREY BASALT 128 178	<u>-</u>
SIZE of perforations in. by in.	BROKEN BROWN LAUA 178 22	3
perforations from	MED HARO GREU BASALT 223 235	_
perforations from	BROKEN BROWN LAVA 236 25	<u>.</u>
perforations from	MED HARD GREY BASALT 254 25	<u></u>
perforations from	HARO GREY BASALT 257 273	
perforations from ft. to ft.		_
(8) SCREENS: Well screen installed		_
Manufacturer's Name		-
Type		-
Slot size Set from ft. to ft.	Work started APR 2 19 68 Completed JUNE 19196	9
Diam. Slot size Set from ft. to ft.	Work started HAR 19 Completed OWE /9196	3
(9) CONSTRUCTION:	(13) PUMP:	
Was well gravel packed?   Yes No Size of gravel:	Manufacturer's Name	
Gravel placed from ft. to ft.	Туре: н.р.	
Was a surface seal provided? Yes □ No To what depth?		-
Material used in seal— (EMEN) (7K00)	Well Driller's Statement:	
Did any strata contain unusable water?   Yes No	This well was drilled under my jurisdiction and this report i	S
Type of water? Depth of strata	true to the best of my knowledge and belief.	
Method of sealing strata off	NAME R.) STRASSER DRILLING (O	
(10) WATER LEVELS: Static level 3 2 ft. below land surface Date 6/5/68	(Person, firm, or corporation) (Type Porint)  Address 8/10 SE SUNSET LANE PORLAND	OL
	564 305 ND 175	-
Artesian pressure lbs. per square inch Date	Driller's well number	
Log-Accepted by:	[Signed] (Well Driller)	
Signed] Date	License No. Date JULI 9, 196	8