NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORT STATE OF OREGON

-			1.3	No. 12	To be	/		
JUL	1	6	100	O w	'ell	No. 31/2	YE	-34

WATER RESOURCES DEPARTMENT,									
SALEM, OREGON 97310									
within 30 days from the date									
of well completion.									

(Do not write above this line)

(Please type or print) WATER RESOURGES REPAIRING.

of well completion. [Do not write al	SALEM. OREGON				
(1) OWNER:	(10) LOCATION OF WELL:				
Name WILTER HULDEN	County GILLIAM Driller's well number				
Address BOX 190	24	R. 2 /E W.M			
ARLINGTON	Bearing and distance from section or subdivisie				
(2) TYPE OF WORK (check):					
New Well 📂 Deepening 🗆 Reconditioning 🗅 Abandon 🗀					
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found				
Rotary Driven Domestic Industrial Municipal	Static level 148 ft. below land s	ft			
Jetted Irrigation Test Well Other	Artesian pressure lbs. per square				
	ins. per square	Finch. Date			
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well b	elow casing 12/4			
2 " Diam from +2 ft. to - 44 ft. Gage # 250	Depth drilled 300 ft. Depth of comple				
	Formation: Describe color, texture, grain size a	and structure of materials			
Diam. from ft. to ft. Gage	and show thickness and nature of each stratur with at least one entry for each change of format	n and aquifer penetrated			
PERFORATIONS: Perforated? Yes Ye	position of Static Water Level and indicate princ	cipal water-bearing strata			
Type of perforator used	MATERIAL	From To SWL			
Size of perforations in. by in.	SOIL	08			
ft. to ft.	CLZY	8 40			
perforations from ft. to ft.	BESELT Black	39 212			
perforations from ft. to ft.	" Black w SS HO	2/2 232			
(7) SCREENS: Well screen installed? Yes Wall	11 Block Seets	232 245			
Manufacturer's Name	11 Black Scoria	291 300			
Type Model No	DBCA	292 300			
Diam Slot size Set from ft. to ft.					
Diam. Slot size Set from ft. to ft.					
(8) WELL TESTS: Drawdown is amount water level is lowered below static level					
pump test made? [] Yes 100 If yes, by whom?					
j: gal./min. with ft. drawdown after hrs.					
" " "					
Bailer test gal./min. with ft. drawdown after hrs.					
an flow g.p.m.					
nperature of water Depth artesian flow encountered ft.	Work started 5 ^ 27 19 80 Complete	d 5~30 1980			
A. Harmonia de la companya del companya de la companya del companya de la company	Date well drilling machine moved off of well	5-31 1980			
(9) CONSTRUCTION:		7 3 1900			
Well seal—Material used PORTLEND CRMENT	Drilling Machine Operator's Certification: This well was constructed under my	direct supervision			
Well sealed from land surface to	Materials used and information reported				
Diameter of well bore to bottom of seal	best knowledge and belief.	4-2 80			
Number of sacks of cement used in well seal 32 sacks	[Signed] (Drijing Machine Operator)	Date 6-3 1980			
How was cement grout placed? TROMIC	Drilling Machine Operator's License No	<i>73</i> 3			
	Water Well Contractor's Certification:				
	This well was drilled under my jurisdic true to the best of my knowledge and beli	cion and this report is			
Was a drive shoe used? Yes No Plugs Size: location ft.	Name Long Bund well	Orilling			
Did any strata contain unusable water? Yes	(Ferson firm or corporation)	(Type or print)			
Type of water? depth of strata	Address Address	***************************************			
Method of sealing strata off	[Signed] Jany Bud	***************************************			
Was well gravel packed? [Yes No Size of gravel:	(Water Well Contra				
Gravel placed from ft. to ft.	Contractor's License No. 544 Date	6-3 19 &			